



健隆投資有限公司

STRONG BASE INVESTMENT LTD.

Unit 17, 11/F., Hewlett Centre, 52-54 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.

Tel: (852) 2793 3293 Fax: (852) 2793 3096



Approval Sheet

(確認書)

編號

Ref. No.

130118-03

日期

Issued Date

2013-1-18

公司名稱

Company Name

產品編號

Part No.

產品種類

Category

產品描述

Description

客戶產品編號

Customer No.

備注

Remarks

STRONG BASE

ISSUER	APPROVER	CHECKER	ENGINEER
	曾雪昭	何春宁	伍晓君

Authorized Signature

客戶簽字

部門				
Department				
簽字				
Signature				

工廠名稱: 宇之亮電子(深圳)有限公司

工廠地址: 廣東省深圳市龍崗區橫崗鎮荷坳村金源工業區

Company Name: Pretty Light (Shen Zhen) Limited

Factory Address: jin-Yuan, Industrial Zone He-Ao Cun, Heng-Gang

Zhen Long-Gang Area, Shen-Zhen City,

TEL: (755) 8976 7353

FAX: (755) 89767754



健隆投資有限公司

STRONG BASE INVESTMENT LTD.

Unit 17, 11/F., Hewlett Centre, 52-54 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.

Tel: (852) 2793 3293

Fax: (852) 2793 3096



PART No: E1-4036CUG1

Client:

Single Chip Light Electricity Characteristic Data

※Absolute Maximum Ratings at Ta=25℃

Parameter	Rating	Unit
Power Dissipation Per Chip	50	mW
Perk Forward Current Per Chip (Frequency 10KHz, 1/10Duty Cycle)	60	mA
Reverse Voltage Per Chip	5	V
Operating Temperature Range	-20~+80	℃
Storage Temperature Range	-20~+85	℃
Storage Humidity	45% ~ 85%	

※Electrical and Optical Characteristics at Ta=25℃

Parameter	Symbol	Condition	Color	Min	Typ	Max	Unit
Forward Voltage Per Chip	VF	IF=20mA	Y-Green	1.9	2.2	2.6	v
Reverse Current	IR	VR=5V	-	-	-	50	uA
Luminous Intensity Per Chip	IV	IF=20mA	Y-Green	8	12	16	mcd
Dominant Wave Length	λ_d	IF=20mA	Y-Green	568	571	573	nm
Normal Forward Current	IF		All Color	5	10	20	mA

Note : Soldering Bath : not more than 4 seconds @260℃. The bottom ends of plastic reflector should be at least 2mm above the solder surface.

Soldering Iron : not more than 3 seconds @300℃ under 30W.



健隆投資有限公司

STRONG BASE INVESTMENT LTD.

Unit 17, 11/F., Hewlett Centre, 52-54 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.

Tel: (852) 2793 3293




Fax: (852) 2793 3096



PART No.: E1-4036CUG1

Client:

PACKAGE DIMENSION(Unit: mm Tolerance: ± 0.5)



INTERNAL CIRCUIT DIAGRAM

Pin Function

