



健隆投資有限公司
STRONG BASE INVESTMENT LTD.

Unit 17, 11/F., Hewlett Centre, 52-54 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.
Tel: (852) 2793 3293 Fax: (852) 2793 3096



Approval Sheet
(確認書)

編號 Ref. No.	150408-01
日期 Issued Date	2015-4-8

公司名稱
Company Name

:

產品編號
Part No.

:

M1-05088CUR1

產品種類
Category

:

数码显示板

產品描述
Description

:

(8*8)陣列、共阴、超高亮红色、黑面散射

客戶產品編號
Customer No.

:

備注
Remarks

:

STRONG BASE			
ISSUER	APPROVER	CHECKER	ENGINEER
	曾雪昭	王金龙	郭清莲

Authorized Signature 客戶簽字				
部門 Department				
簽字 Signature				

工廠名稱:字之亮電子(深圳)有限公司

工廠地址:廣東省深圳市龍崗區橫崗鎮荷坳村金源工業區

Company Name: Pretty Light (Shen Zhen) Limited

Factory Address:jin-Yuan,Industrial Zone He-Ao Cun,Heng-Gang

Zhen Long-Gang Area,Shen-Zhen City,

TEL: (755) 8976 7353

FAX: (755) 89767754



健隆投資有限公司

STRONG BASE INVESTMENT LTD.

Unit 17, 11/F., Hewlett Centre, 52-54 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.

Tel: (852) 2793 3293

Fax: (852) 2793 3096



PART No: M1-05088CUR1

Client:

Single Chip Light Electricity Characteristic Data

※Absolute Maximum Ratings at Ta=25℃

Parameter	Rating	Unit
Power Dissipation Per Chip	80	mW
Perk Forward Current Per Chip (Frequency 10KHz,1/10Duty Cycle)	60	mA
Reverse Voltage Per Chip	5	V
Operating Temperature Range	-20~+80	℃
Storage Temperature Range	-20~+85	℃
Storage Humidity	45%~85%	

※Electrical and Optical Characteristics at Ta=25℃

Parameter	Symbol	Condition	Color	Min	Typ	Max	Unit
Forward Voltage Per Chip	VF	IF=10mA	Red	1.7	2.0	2.5	V
			-	-	-	-	
			-	-	-	-	
			-	-	-	-	
Reverse Current	IR	VR=5V	-	-	-	50	uA
Luminous Intensity Per Chip	IV	IF=10mA	Red	30	45	60	mcd
			-	-	-	-	
			-	-	-	-	
			-	-	-	-	
Dominant Wave Length	λ_d	IF=10mA	Red	625	630	640	nm
			-	-	-	-	
			-	-	-	-	
			-	-	-	-	
Normal Forward Current	IF		All Color	5	10	20	mA

Note : Soldering Bath : not more than 4 seconds @260℃ ◦ The bottom ends of plastic reflector should be at least 2mm above the solder surface ◦

Soldering Iron : not more than 3 seconds @300℃ under 30W ◦

