



PIN	1	2	3	4	5	6	7	8	9	10	11	12
BP	1E	1D	1C	DP1	2E	2D	2C	DP2	3E	3D	3C	3B
PIN	13	14	15	16	17	18	19	20	21	22	23	24
BP	3A	3F	3G	2B	2A	2F	2G	1B	1A	1F	1G	BP

- ALL DIMENSIONS ARE IN mm WITH ± 0.20 TOLERANCE UNLESS OTHERWISE SPECIFIED.
- VIEWING ANGLE: 6:00 O'CLOCK.
- VIEWING MODE: POSITIVE/RELECTIVE
- DISPLAY TYPE : TN
- CONNECTION: PIN
- FLUID SPECIFICATION:
 DRIVING VOLTAGE: 5.0V
 MULTIPLEX LEVEL: STATIC
 OPERATING TEMP. : -10°C -- $+60^{\circ}\text{C}$
 STORAGE TEMP. : -20°C -- $+70^{\circ}\text{C}$

确认此型号所有图纸; 签字确认:	序号	内容	绘图	日期	厦门精显电子有限公司 XIAMEN PRECISE DISPLAY CO., LTD.				
	修改	管脚跨距由24.6改为25.4MM	WLF	2012.03.09					
	改	管脚跨距由25.4改为24.6MM	CMH	2011.09.06	客户编号: GYTN0804AP	版号: 03			
		改管脚长度公差为 ± 0.5 MM	CMH	2011.01.07	绘图: XXX	复核: XXX	日期: 2012.03.09	审核: XXX	批准: XXX