

## PHOTOTRANSISTOR SPECIFICATION

PART NUMBER: 3244 SC	3mm Phototransistor, Water Clear Lens																																																																										
<p style="margin-top: 10px;">Tolerance: ±0.25(0.01) Unit: mm (inch)</p>	<p>Absolute Maximum Rating (25°C unless otherwise notes)</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>Collector to Emitter Breakdown Voltage <math>V_{BR\ CE0}</math></td> <td style="text-align: right;">30V</td> </tr> <tr> <td>Emitter to Collector Breakdown Voltage</td> <td style="text-align: right;">5V</td> </tr> <tr> <td>Operating Temperature Range</td> <td style="text-align: right;">+40 ~ +85°C</td> </tr> <tr> <td>Lead Soldering Temperature (4mm for 5 Sec)</td> <td style="text-align: right;">260°C</td> </tr> <tr> <td>Power Dissipation at (or below) 25°C Free Air Temperature</td> <td style="text-align: right;">100mW</td> </tr> <tr> <td>Storage Temperature Range</td> <td style="text-align: right;">-40+85°C</td> </tr> </table> <p>Electrical And Radiant Characteristics (Ta=25°C)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Symbol</th> <th>Parameter</th> <th>Min</th> <th>Typ.</th> <th>Max.</th> <th>Unit</th> <th>Condition</th> </tr> </thead> <tbody> <tr> <td><math>V_{BRECO}</math></td> <td>Collector to emitter Breakdown Voltage</td> <td>30</td> <td>-</td> <td>-</td> <td rowspan="2">V</td> <td><math>I_C=100\mu A</math> <math>I_B=0</math></td> </tr> <tr> <td><math>V_{BREC}</math></td> <td>Emitter to Collector Breakdown Voltage</td> <td>5</td> <td>-</td> <td>-</td> <td><math>I_E=100\mu A</math> <math>I_B=0</math></td> </tr> <tr> <td><math>V_{CE(SAT)}</math></td> <td>Collector to Emitter Breakdown Voltage</td> <td>-</td> <td>-</td> <td>0.8</td> <td></td> <td><math>I_C=0.1mA</math> <math>H=2.5mW/cm^2</math></td> </tr> <tr> <td><math>I_D</math></td> <td>Dark Current</td> <td>-</td> <td>-</td> <td>100</td> <td>nA</td> <td><math>V_{CE}=10V</math> <math>H=0M_{W/CM^2}</math></td> </tr> <tr> <td><math>T_R</math></td> <td>Rise Time (10% to 90%)</td> <td>-</td> <td>3</td> <td>-</td> <td rowspan="2">uS</td> <td rowspan="2"><math>V_{CE}=5V, I_C=1mA</math> <math>R_L=100ohms</math></td> </tr> <tr> <td><math>T_F</math></td> <td>Fall Time (90% to 10)</td> <td>-</td> <td>3</td> <td>-</td> </tr> <tr> <td rowspan="4"><math>I_{(ON)}</math></td> <td rowspan="4">On State Collector Current</td> <td>1</td> <td>-</td> <td>2</td> <td rowspan="4">mA</td> <td rowspan="4"><math>V_{CE}=5V</math> <math>E_e=1mW/cm^2</math> <math>\lambda=940nm</math></td> </tr> <tr> <td>2</td> <td>-</td> <td>4</td> </tr> <tr> <td>3</td> <td>-</td> <td>8</td> </tr> <tr> <td>4</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Collector to Emitter Breakdown Voltage $V_{BR\ CE0}$	30V	Emitter to Collector Breakdown Voltage	5V	Operating Temperature Range	+40 ~ +85°C	Lead Soldering Temperature (4mm for 5 Sec)	260°C	Power Dissipation at (or below) 25°C Free Air Temperature	100mW	Storage Temperature Range	-40+85°C	Symbol	Parameter	Min	Typ.	Max.	Unit	Condition	$V_{BRECO}$	Collector to emitter Breakdown Voltage	30	-	-	V	$I_C=100\mu A$ $I_B=0$	$V_{BREC}$	Emitter to Collector Breakdown Voltage	5	-	-	$I_E=100\mu A$ $I_B=0$	$V_{CE(SAT)}$	Collector to Emitter Breakdown Voltage	-	-	0.8		$I_C=0.1mA$ $H=2.5mW/cm^2$	$I_D$	Dark Current	-	-	100	nA	$V_{CE}=10V$ $H=0M_{W/CM^2}$	$T_R$	Rise Time (10% to 90%)	-	3	-	uS	$V_{CE}=5V, I_C=1mA$ $R_L=100ohms$	$T_F$	Fall Time (90% to 10)	-	3	-	$I_{(ON)}$	On State Collector Current	1	-	2	mA	$V_{CE}=5V$ $E_e=1mW/cm^2$ $\lambda=940nm$	2	-	4	3	-	8	4	-	-
Collector to Emitter Breakdown Voltage $V_{BR\ CE0}$	30V																																																																										
Emitter to Collector Breakdown Voltage	5V																																																																										
Operating Temperature Range	+40 ~ +85°C																																																																										
Lead Soldering Temperature (4mm for 5 Sec)	260°C																																																																										
Power Dissipation at (or below) 25°C Free Air Temperature	100mW																																																																										
Storage Temperature Range	-40+85°C																																																																										
Symbol	Parameter	Min	Typ.	Max.	Unit	Condition																																																																					
$V_{BRECO}$	Collector to emitter Breakdown Voltage	30	-	-	V	$I_C=100\mu A$ $I_B=0$																																																																					
$V_{BREC}$	Emitter to Collector Breakdown Voltage	5	-	-		$I_E=100\mu A$ $I_B=0$																																																																					
$V_{CE(SAT)}$	Collector to Emitter Breakdown Voltage	-	-	0.8		$I_C=0.1mA$ $H=2.5mW/cm^2$																																																																					
$I_D$	Dark Current	-	-	100	nA	$V_{CE}=10V$ $H=0M_{W/CM^2}$																																																																					
$T_R$	Rise Time (10% to 90%)	-	3	-	uS	$V_{CE}=5V, I_C=1mA$ $R_L=100ohms$																																																																					
$T_F$	Fall Time (90% to 10)	-	3	-																																																																							
$I_{(ON)}$	On State Collector Current	1	-	2	mA	$V_{CE}=5V$ $E_e=1mW/cm^2$ $\lambda=940nm$																																																																					
		2	-	4																																																																							
		3	-	8																																																																							
		4	-	-																																																																							

PART NUMBER: 5243 SC	5mm Phototransistor, Water Clear Lens																																																																										
<p style="margin-top: 10px;">Tolerance: ±0.25 (0.01) Unit: mm(inch)</p>	<p>Absolute Maximum Rating (25°C unless otherwise notes)</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>Collector to Emitter Breakdown Voltage <math>V_{BR\ CE0}</math></td> <td style="text-align: right;">30V</td> </tr> <tr> <td>Emitter to Collector Breakdown Voltage</td> <td style="text-align: right;">5V</td> </tr> <tr> <td>Operating Temperature Range</td> <td style="text-align: right;">+40 ~ +85°C</td> </tr> <tr> <td>Lead Soldering Temperature (4mm for 5 Sec)</td> <td style="text-align: right;">260°C</td> </tr> <tr> <td>Power Dissipation at (or below) 25°C Free Air Temperature</td> <td style="text-align: right;">100mW</td> </tr> <tr> <td>Storage Temperature Range</td> <td style="text-align: right;">-40+85°C</td> </tr> </table> <p>Electrical And Radiant Characteristics (Ta=25°C)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Symbol</th> <th>Parameter</th> <th>Min</th> <th>Typ.</th> <th>Max.</th> <th>Unit</th> <th>Condition</th> </tr> </thead> <tbody> <tr> <td><math>V_{BRECO}</math></td> <td>Collector to emitter Breakdown Voltage</td> <td>30</td> <td>-</td> <td>-</td> <td rowspan="2">V</td> <td><math>I_C=100\mu A</math> <math>I_B=0</math></td> </tr> <tr> <td><math>V_{BREC}</math></td> <td>Emitter to Collector Breakdown Voltage</td> <td>5</td> <td>-</td> <td>-</td> <td><math>I_E=100\mu A</math> <math>I_B=0</math></td> </tr> <tr> <td><math>V_{CE(SAT)}</math></td> <td>Collector to Emitter Breakdown Voltage</td> <td>-</td> <td>-</td> <td>0.8</td> <td></td> <td><math>I_C=0.1mA</math> <math>H=2.5mW/cm^2</math></td> </tr> <tr> <td><math>I_D</math></td> <td>Dark Current</td> <td>-</td> <td>-</td> <td>100</td> <td>nA</td> <td><math>V_{CE}=10V</math> <math>H=0M_{W/CM^2}</math></td> </tr> <tr> <td><math>T_R</math></td> <td>Rise Time (10% to 90%)</td> <td>-</td> <td>3</td> <td>-</td> <td rowspan="2">uS</td> <td rowspan="2"><math>V_{CE}=5V, I_C=1mA</math> <math>R_L=100ohms</math></td> </tr> <tr> <td><math>T_F</math></td> <td>Fall Time (90% to 10)</td> <td>-</td> <td>3</td> <td>-</td> </tr> <tr> <td rowspan="4"><math>I_{(ON)}</math></td> <td rowspan="4">On State Collector Current</td> <td>1</td> <td>-</td> <td>2</td> <td rowspan="4">mA</td> <td rowspan="4"><math>V_{CE}=5V</math> <math>E_e=1mW/cm^2</math> <math>\lambda=940nm</math></td> </tr> <tr> <td>2</td> <td>-</td> <td>4</td> </tr> <tr> <td>3</td> <td>-</td> <td>8</td> </tr> <tr> <td>4</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Collector to Emitter Breakdown Voltage $V_{BR\ CE0}$	30V	Emitter to Collector Breakdown Voltage	5V	Operating Temperature Range	+40 ~ +85°C	Lead Soldering Temperature (4mm for 5 Sec)	260°C	Power Dissipation at (or below) 25°C Free Air Temperature	100mW	Storage Temperature Range	-40+85°C	Symbol	Parameter	Min	Typ.	Max.	Unit	Condition	$V_{BRECO}$	Collector to emitter Breakdown Voltage	30	-	-	V	$I_C=100\mu A$ $I_B=0$	$V_{BREC}$	Emitter to Collector Breakdown Voltage	5	-	-	$I_E=100\mu A$ $I_B=0$	$V_{CE(SAT)}$	Collector to Emitter Breakdown Voltage	-	-	0.8		$I_C=0.1mA$ $H=2.5mW/cm^2$	$I_D$	Dark Current	-	-	100	nA	$V_{CE}=10V$ $H=0M_{W/CM^2}$	$T_R$	Rise Time (10% to 90%)	-	3	-	uS	$V_{CE}=5V, I_C=1mA$ $R_L=100ohms$	$T_F$	Fall Time (90% to 10)	-	3	-	$I_{(ON)}$	On State Collector Current	1	-	2	mA	$V_{CE}=5V$ $E_e=1mW/cm^2$ $\lambda=940nm$	2	-	4	3	-	8	4	-	-
Collector to Emitter Breakdown Voltage $V_{BR\ CE0}$	30V																																																																										
Emitter to Collector Breakdown Voltage	5V																																																																										
Operating Temperature Range	+40 ~ +85°C																																																																										
Lead Soldering Temperature (4mm for 5 Sec)	260°C																																																																										
Power Dissipation at (or below) 25°C Free Air Temperature	100mW																																																																										
Storage Temperature Range	-40+85°C																																																																										
Symbol	Parameter	Min	Typ.	Max.	Unit	Condition																																																																					
$V_{BRECO}$	Collector to emitter Breakdown Voltage	30	-	-	V	$I_C=100\mu A$ $I_B=0$																																																																					
$V_{BREC}$	Emitter to Collector Breakdown Voltage	5	-	-		$I_E=100\mu A$ $I_B=0$																																																																					
$V_{CE(SAT)}$	Collector to Emitter Breakdown Voltage	-	-	0.8		$I_C=0.1mA$ $H=2.5mW/cm^2$																																																																					
$I_D$	Dark Current	-	-	100	nA	$V_{CE}=10V$ $H=0M_{W/CM^2}$																																																																					
$T_R$	Rise Time (10% to 90%)	-	3	-	uS	$V_{CE}=5V, I_C=1mA$ $R_L=100ohms$																																																																					
$T_F$	Fall Time (90% to 10)	-	3	-																																																																							
$I_{(ON)}$	On State Collector Current	1	-	2	mA	$V_{CE}=5V$ $E_e=1mW/cm^2$ $\lambda=940nm$																																																																					
		2	-	4																																																																							
		3	-	8																																																																							
		4	-	-																																																																							