

APDI-55-3G-K

OVERVIEW

APDI-55-3G-K is the InGaAs avalanche photodiode coupled to an optical fiber and packaged into a hermetic case

MAIN FEATURES

- Bandwidth 3 GHz
- Spectral range: 800 - 1650 nm
- Typical responsivity: 1.0 A/W at 1310 nm and M = 1
- Package types: coaxial with or without bracket
- Low dark current typ. 3-5 nA @ 0.95 V_{BR}

APPLICATIONS

- Optical fiber communication systems
- OTDR

ORDERING INFORMATION

APDI-55-3G-K-X-X-7-X-X-X

Optical matching

RM: back reflection -30 dB, optical matching

Case type

U: compact coaxial
B: compact coaxial with double-sided bracket
T: 14 pins DIL with thermal stability
E: 14 pins DIL with thermal stability

Fiber type

SMT: SM, [Corning Titania-Clad](#), furcation tubing Ø0.9 mm, ultrasmall bending radius 2.5 mm
SM1: SM, G.657.A1, [Corning SMF-28 Ultra](#), furcation tubing Ø0.9 mm or **BSM1** Ø0.25mm
SM3: SM, G.657.B3, [Corning ClearCurve ZBL](#), furcation tubing Ø0.9 mm or **BSM3** Ø0.25mm
MM5: MM, [50/125.OM2](#), furcation tubing Ø0.9 mm
MM6: MM, [62.5/125.OM1](#), furcation tubing Ø0.9 mm
 Other type: on request

Connector type

FA: FC/APC (SM1, SM3, SMT) **FU:** FC/UPC (SM1, SM3, SMT, MM5, MM6)
SA: SC/APC (SM1) **SU:** SC/UPC (SM1)
N: no connector
 Other type: on request

Fiber length

0.5: 500+/-50 mm
1.0: 1000+/-100 mm
 Other length: on request

APDI-55-3G-K

ABSOLUTE MAXIMUM RATINGS




Parameter		Value	Unit	Conditions
Reverse current	I_R	2	mA	
Forward current	I_F	10	mA	
Operating temperature	T_{op}	-40 ÷ +85	°C	Package U, B
Operating temperature	T_{op}	-40 ÷ +50	°C	Package T, E
Storage temperature	T_{stg}	-40 ÷ +85	°C	
Soldering temperature	T_{sold}	260	°C	Max. 5 seconds

ELECTRICAL-OPTICAL CHARACTERISTICS (T = 25 °C)

Parameter		Min	Typ	Max	Unit	Conditions
Operating wavelength		800		1650	nm	
Responsivity @ M=1	R	0.95	1.05		A/W	$\lambda = 1310 \text{ nm}$
Responsivity @ 0.95 V_{BR}	R	10	25			$\lambda = 1310 \text{ nm}, V_R = 0.95 V_{BR}$
Return loss	RL	25	30		dB	
Breakdown voltage	V_{BR}	40	45	50		$I_d = 100 \mu\text{A}$
Breakdown voltage temperature coefficient $\Delta V_{BR}/\Delta T$	δ	0.08	0.10	0.12	V/°C	T = 25 °C
Dark current	I_d		4	10	nA	$V_R = 0.95 V_{BR}$
Total capacitance	C_t		0.68	0.8	pF	f = 1 MHz
Chip capacitance	C_{chip}		0.38	0.5	pF	f = 1 MHz
Bandwidth	BW		3		GHz	M = 10

APDI-55-3G-K

CHARACTERISTICS (T = 25 °C)




APDI-55-3G-K


PACKAGE TYPE AND ELECTRICAL PINOUT

PACKAGE U


SIDE VIEW



BACK VIEW



PINOUT #7




Connector FC/UPC, FC/APC, no connector, or by request


Fiber length 500+/-50, 1000+/-100, or by request

PACKAGE B


SIDE VIEW



BACK VIEW



PINOUT #7




Connector FC/UPC, FC/APC, no connector, or by request



Fiber length 500+/-50, 1000+/-100, or by request

PACKAGE T

FRONT VIEW



BOTTOM VIEW



PINOUT #5, #7


- 1.TEC Anode
- 2.-
- 3.-
- 4.-
- 5.PD Case
- 6.-
- 7.PD Cathode
- 8.PD Anode
- 9.-
- 10.-
- 11.Thermistor
- 12.Thermistor
- 13.-
- 14.TEC Cathode

TEC: $I_{max}=0.7A$, $U_{max}=3.9V$, $Q_{max}=1.4W$,
 $ACR=4.7\text{ Ohm}$, $\Delta T_{max}=72\text{ K}$

Thermistor:
 $R_t=10*EXP(3600*(1/T[K]-1/298))\text{ kOhm}$

APDI-55-3G-K

PACKAGE TYPE AND ELECTRICAL PINOUT



APDI-55-3G-K

Characteristics, data, materials and structures specified in this datasheet are subject to change without notice. Please refer to the latest specification before use of the products.

Safety and handling cautions

1. Avoid smashing and burning of the module. Avoid storing and using the module in conditions where water, organic solvents or aggressive acids or bases may contact the module or where there is a possibility of exposure to corrosive gases, explosive gases, dust, salinity or other harsh conditions. The module should be disposed as special industrial waste.
2. Exceeding absolute maximal ratings even for a short time can cause permanent damage of the module.
3. The module is sensitive to and can be broken by ESD (static electricity).

Conflict Minerals Policy Statement

LasersCom LLC achieves business objectives and customer needs with social responsibility. We do not support or contribute to the violence and human rights violations associated with the mining of conflict minerals coming from Conflict Regions according to US "Dodd-Frank Act". When possible, our suppliers' conflict mineral statements are reviewed. We do not directly purchase Conflict Minerals from any source and do not knowingly procure any parts and products containing Conflict Minerals from Conflict Regions.

RoHS Compliance Statement

Restriction of Hazardous Substances (RoHS) directive (Directive 2011/65/EC amended with Directive (EU) 2015/863) is the directive aimed at reducing the harmful environmental impact of waste electrical equipment by restricting the use of known dangerous substances. Based on information received from our supply sources, LasersCom LLC hereby states that the banned substances listed in the RoHS directive are not found in the parts and materials used above the threshold level listed other than exceptions approved by the European Commission.

REACH Compliance Statement

Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) is a European Union regulation 1907/2006/EC that addresses the production and use of chemical substances, and their potential impacts on human health and the environment. Based on information received from our supply sources, LasersCom LLC hereby states compliance of the parts and materials used in manufacturing to REACH regulation. LasersCom LLC does not manufacture or import any substances or preparations as defined under REACH.