



# Optocoupler, Phototransistor Output, Low Input Current



## FEATURES

- Good CTR linearity depending on forward current
- Low CTR degradation
- High collector emitter voltage,  $V_{CEO} = 55\text{ V}$
- Isolation test voltage,  $5300\text{ V}_{RMS}$
- Low coupling capacitance
- End stackable, 0.100" (2.54 mm) spacing
- High common mode transient immunity
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

## APPLICATIONS

- Telecom
- Industrial controls
- Battery powered equipment
- Office machines

## AGENCY APPROVALS

The safety application model number covering all products in this datasheet is SFH618A. This model number should be used when consulting safety agency documents.


- UL1577
- cUL
- CSA
- DIN EN 60747-5-5 (VDE 0884-5) available with option 1
- BSI
- FIMKO

## DESCRIPTION

The SFH618A (DIP) and SFH6186 (SMD) feature a high current transfer ratio, low coupling capacitance and high isolation voltage. These couplers have a GaAs infrared diode emitter, which is optically coupled to silicon planar phototransistor detector, and is incorporated in a plastic DIP-4 or SMD package.

The coupling devices are designed for signal transmission between two electrically separated circuits. The couplers are end-stackable with 2.54 mm lead spacing. Creepage and clearance distances of > 8 mm achieved with option 6.

## ORDERING INFORMATION



| AGENCY<br>CERTIFIED/PACKAGE | CTR (%)                   |                                                    |                           |                                            |
|-----------------------------|---------------------------|----------------------------------------------------|---------------------------|--------------------------------------------|
|                             | 1 mA                      |                                                    |                           |                                            |
| <b>UL, cUL</b>              | <b>63 to 125</b>          | <b>100 to 200</b>                                  | <b>160 to 320</b>         | <b>250 to 500</b>                          |
| DIP-4                       | SFH618A-2                 | SFH618A-3                                          | SFH618A-4                 | SFH618A-5                                  |
| DIP-4, 400 mil, option 6    | -                         | SFH618A-3X006                                      | -                         | -                                          |
| SMD-4, option 7             | -                         | -                                                  | -                         | SFH618A-5X007T <sup>(1)</sup>              |
| SMD-4, option 9             | SFH6186-2T <sup>(1)</sup> | SFH6186-3T <sup>(1)</sup> , SFH6186-3T1            | SFH6186-4T <sup>(1)</sup> | SFH6186-5T <sup>(1)</sup> ,<br>SFH6186-5T1 |
| <b>VDE, UL, cUL</b>         | <b>63 to 125</b>          | <b>100 to 200</b>                                  | <b>160 to 320</b>         | <b>250 to 500</b>                          |
| DIP-4                       | -                         | SFH618A-3X001                                      | SFH618A-4X001             | -                                          |
| DIP-4, 400 mil, option 6    | -                         | SFH618A-3X016                                      | SFH618A-4X016             | SFH618A-5X016                              |
| SMD-4, option 7             | -                         | SFH618A-3X017T <sup>(1)</sup>                      | -                         | SFH618A-5X017T <sup>(1)</sup>              |
| SMD-4, option 9             | -                         | SFH6186-3X001T <sup>(1)</sup> ,<br>SFH6186-3X001T1 | SFH6186-4X001T            | SFH6186-5X001T <sup>(1)</sup>              |

## Notes

- Additional options may be possible, please contact sales office

<sup>(1)</sup> Also available in tubes, do not put T to the end



| <b>ABSOLUTE MAXIMUM RATINGS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                         |            |             |                    |
|--------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|------------|-------------|--------------------|
| PARAMETER                                                                                              | TEST CONDITION                                                          | SYMBOL     | VALUE       | UNIT               |
| <b>INPUT</b>                                                                                           |                                                                         |            |             |                    |
| Reverse voltage                                                                                        |                                                                         | $V_R$      | 6           | V                  |
| Power dissipation                                                                                      |                                                                         | $P_{diss}$ | 70          | mW                 |
| Forward current                                                                                        |                                                                         | $I_F$      | 60          | mA                 |
| <b>OUTPUT</b>                                                                                          |                                                                         |            |             |                    |
| Collector emitter voltage                                                                              |                                                                         | $V_{CEO}$  | 55          | V                  |
| Emitter collector voltage                                                                              |                                                                         | $V_{ECO}$  | 7           | V                  |
| Collector current                                                                                      |                                                                         | $I_C$      | 50          | mA                 |
|                                                                                                        | $t_p \leq 1\text{ ms}$                                                  | $I_C$      | 100         | mA                 |
| Power dissipation                                                                                      |                                                                         | $P_{diss}$ | 150         | mW                 |
| <b>COUPLER</b>                                                                                         |                                                                         |            |             |                    |
| Storage temperature range                                                                              |                                                                         | $T_{stg}$  | -55 to +150 | $^{\circ}\text{C}$ |
| Ambient temperature range                                                                              |                                                                         | $T_{amb}$  | -55 to +100 | $^{\circ}\text{C}$ |
| Junction temperature                                                                                   |                                                                         | $T_j$      | 125         | $^{\circ}\text{C}$ |
| Soldering temperature                                                                                  | max. 10 s, dip soldering distance to seating plane $\geq 1.5\text{ mm}$ | $T_{sld}$  | 260         | $^{\circ}\text{C}$ |

**Note**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability




Fig. 1 - Permissible Power Dissipation vs. Ambient Temperature



| ELECTRICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                              |           |             |      |      |      |               |
|---------------------------------------------------------------------------------------------------|----------------------------------------------|-----------|-------------|------|------|------|---------------|
| PARAMETER                                                                                         | TEST CONDITION                               | PART      | SYMBOL      | MIN. | TYP. | MAX. | UNIT          |
| INPUT                                                                                             |                                              |           |             |      |      |      |               |
| Forward voltage                                                                                   | $I_F = 5\text{ mA}$                          |           | $V_F$       | -    | 1.1  | 1.5  | V             |
| Reverse current                                                                                   | $V_R = 6\text{ V}$                           |           | $I_R$       | -    | 0.01 | 10   | $\mu\text{A}$ |
| Capacitance                                                                                       | $V_R = 0\text{ V}$ , $f = 1\text{ MHz}$      |           | $C_O$       | -    | 25   | -    | pF            |
| Thermal resistance                                                                                |                                              |           | $R_{thja}$  | -    | 1070 | -    | K/W           |
| OUTPUT                                                                                            |                                              |           |             |      |      |      |               |
| Collector emitter leakage current                                                                 | $V_{CE} = 10\text{ V}$                       |           | $I_{CEO}$   | -    | 10   | 200  | nA            |
| Collector emitter capacitance                                                                     | $V_{CE} = 5\text{ V}$ , $f = 1\text{ MHz}$   |           | $C_{CE}$    | -    | 7    | -    | pF            |
| Thermal resistance                                                                                |                                              |           | $R_{thja}$  | -    | 500  | -    | K/W           |
| COUPLER                                                                                           |                                              |           |             |      |      |      |               |
| Collector emitter saturation voltage                                                              | $I_C = 0.32\text{ mA}$ , $I_F = 1\text{ mA}$ | SFH618A-2 | $V_{CEsat}$ | -    | 0.25 | 0.4  | V             |
|                                                                                                   |                                              | SFH6186-2 | $V_{CEsat}$ | -    | 0.25 | 0.4  | V             |
|                                                                                                   | $I_C = 0.5\text{ mA}$ , $I_F = 1\text{ mA}$  | SFH618A-3 | $V_{CEsat}$ | -    | 0.25 | 0.4  | V             |
|                                                                                                   |                                              | SFH6186-3 | $V_{CEsat}$ | -    | 0.25 | 0.4  | V             |
|                                                                                                   | $I_C = 0.8\text{ mA}$ , $I_F = 1\text{ mA}$  | SFH618A-4 | $V_{CEsat}$ | -    | 0.25 | 0.4  | V             |
|                                                                                                   |                                              | SFH6186-4 | $V_{CEsat}$ | -    | 0.25 | 0.4  | V             |
|                                                                                                   | $I_C = 1.25\text{ mA}$ , $I_F = 1\text{ mA}$ | SFH618A-5 | $V_{CEsat}$ | -    | 0.25 | 0.4  | V             |
|                                                                                                   |                                              | SFH6186-5 | $V_{CEsat}$ | -    | 0.25 | 0.4  | V             |
| Coupling capacitance                                                                              |                                              |           | $C_C$       | -    | 0.25 | -    | pF            |

**Note**

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements

| CURRENT TRANSFER RATIO ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                 |           |        |      |      |      |      |
|-----------------------------------------------------------------------------------------------|-------------------------------------------------|-----------|--------|------|------|------|------|
| PARAMETER                                                                                     | TEST CONDITION                                  | PART      | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| $I_C/I_F$                                                                                     | $I_F = 1\text{ mA}$ , $V_{CE} = 0.5\text{ V}$   | SFH618A-2 | CTR    | 63   | -    | 125  | %    |
|                                                                                               |                                                 | SFH6186-2 | CTR    | 63   | -    | 125  | %    |
|                                                                                               | $I_F = 0.5\text{ mA}$ , $V_{CE} = 1.5\text{ V}$ | SFH618A-2 | CTR    | 32   | 75   | -    | %    |
|                                                                                               |                                                 | SFH6186-2 | CTR    | 32   | 75   | -    | %    |
|                                                                                               | $I_F = 1\text{ mA}$ , $V_{CE} = 0.5\text{ V}$   | SFH618A-3 | CTR    | 100  | -    | 200  | %    |
|                                                                                               |                                                 | SFH6186-3 | CTR    | 100  | -    | 200  | %    |
|                                                                                               | $I_F = 0.5\text{ mA}$ , $V_{CE} = 1.5\text{ V}$ | SFH618A-3 | CTR    | 50   | 120  | -    | %    |
|                                                                                               |                                                 | SFH6186-3 | CTR    | 50   | 120  | -    | %    |
|                                                                                               | $I_F = 1\text{ mA}$ , $V_{CE} = 0.5\text{ V}$   | SFH618A-4 | CTR    | 160  | -    | 320  | %    |
|                                                                                               |                                                 | SFH6186-4 | CTR    | 160  | -    | 320  | %    |
|                                                                                               | $I_F = 0.5\text{ mA}$ , $V_{CE} = 1.5\text{ V}$ | SFH618A-4 | CTR    | 80   | 200  | -    | %    |
|                                                                                               |                                                 | SFH6186-4 | CTR    | 80   | 200  | -    | %    |
|                                                                                               | $I_F = 1\text{ mA}$ , $V_{CE} = 0.5\text{ V}$   | SFH618A-5 | CTR    | 250  | -    | 500  | %    |
|                                                                                               |                                                 | SFH6186-5 | CTR    | 250  | -    | 500  | %    |
|                                                                                               | $I_F = 0.5\text{ mA}$ , $V_{CE} = 1.5\text{ V}$ | SFH618A-5 | CTR    | 125  | 300  | -    | %    |
|                                                                                               |                                                 | SFH6186-5 | CTR    | 125  | 300  | -    | %    |

| SWITCHING CHARACTERISTICS (T <sub>amb</sub> = 25 °C, unless otherwise specified) |                                                                      |                  |      |      |      |      |
|----------------------------------------------------------------------------------|----------------------------------------------------------------------|------------------|------|------|------|------|
| PARAMETER                                                                        | TEST CONDITION                                                       | SYMBOL           | MIN. | TYP. | MAX. | UNIT |
| Turn on time                                                                     | V <sub>CC</sub> = 5 V, I <sub>C</sub> = 2 mA, R <sub>L</sub> = 100 Ω | t <sub>on</sub>  | -    | 6    | -    | μs   |
| Rise time                                                                        | V <sub>CC</sub> = 5 V, I <sub>C</sub> = 2 mA, R <sub>L</sub> = 100 Ω | t <sub>r</sub>   | -    | 3.5  | -    | μs   |
| Turn off time                                                                    | V <sub>CC</sub> = 5 V, I <sub>C</sub> = 2 mA, R <sub>L</sub> = 100 Ω | t <sub>off</sub> | -    | 5.5  | -    | μs   |
| Fall time                                                                        | V <sub>CC</sub> = 5 V, I <sub>C</sub> = 2 mA, R <sub>L</sub> = 100 Ω | t <sub>f</sub>   | -    | 5    | -    | μs   |




Fig. 2 - Test Circuit




Fig. 3 - Parameter and Limit Definition

| SAFETY AND INSULATION RATINGS                |                                                    |                   |                    |                   |
|----------------------------------------------|----------------------------------------------------|-------------------|--------------------|-------------------|
| PARAMETER                                    | TEST CONDITION                                     | SYMBOL            | VALUE              | UNIT              |
| Climatic classification                      | According to IEC 68 part 1                         |                   | 55 / 115 / 21      |                   |
| Pollution degree                             | According to DIN VDE 0109                          |                   | 2                  |                   |
| Comparative tracking index                   | Insulation group IIIa                              | CTI               | 175                |                   |
| Maximum rated withstanding isolation voltage | According to UL1577, t = 1 min                     | V <sub>ISO</sub>  | 4470               | V <sub>RMS</sub>  |
| Tested withstanding isolation voltage        | According to UL1577, t = 1 s                       | V <sub>ISO</sub>  | 5300               | V <sub>RMS</sub>  |
| Maximum transient isolation voltage          | According to DIN EN 60747-5-5                      | V <sub>IOTM</sub> | 8000               | V <sub>peak</sub> |
| Maximum repetitive peak isolation voltage    | According to DIN EN 60747-5-5                      | V <sub>IORM</sub> | 890                | V <sub>peak</sub> |
| Isolation resistance                         | T <sub>amb</sub> = 25 °C, V <sub>IO</sub> = 500 V  | R <sub>IO</sub>   | ≥ 10 <sup>12</sup> | Ω                 |
|                                              | T <sub>amb</sub> = 100 °C, V <sub>IO</sub> = 500 V | R <sub>IO</sub>   | ≥ 10 <sup>11</sup> | Ω                 |
| Output safety power                          |                                                    | P <sub>SO</sub>   | 700                | mW                |
| Input safety current                         |                                                    | I <sub>SI</sub>   | 400                | mA                |
| Input safety temperature                     |                                                    | T <sub>S</sub>    | 175                | °C                |
| Creepage distance                            | DIP-4                                              |                   | ≥ 7                | mm                |
| Clearance distance                           |                                                    |                   | ≥ 7                | mm                |
| Creepage distance                            | DIP-4, 400 mil, option 6                           |                   | ≥ 8                | mm                |
| Clearance distance                           |                                                    |                   | ≥ 8                | mm                |
| Creepage distance                            | SMD-4, option 7 and option 9                       |                   | ≥ 7                | mm                |
| Clearance distance                           |                                                    |                   | ≥ 7                | mm                |
| Insulation thickness                         |                                                    | DTI               | ≥ 0.4              | mm                |

#### Note

- As per DIN EN 60747-5-5, § 7.4.3.8.2, this optocoupler is suitable for “safe electrical insulation” only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits

#### TYPICAL CHARACTERISTICS (T<sub>amb</sub> = 25 °C, unless otherwise specified)




Fig. 4 - Forward Voltage vs. Forward Current




Fig. 5 - Collector Current vs. Collector Emitter Voltage




Fig. 6 - Collector Emitter Current vs. Ambient Temperature




Fig. 9 - Normalized Current Transfer Ratio vs. Ambient Temperature (sat.)




Fig. 7 - Collector Current vs. Collector Emitter Voltage




Fig. 10 - Normalized Current Transfer Ratio vs. Ambient Temperature (non-sat.)




Fig. 8 - Collector Emitter Voltage vs. Ambient Temperature




Fig. 11 - Current Transfer Ratio vs. Forward Current (sat.)




Fig. 12 - Current Transfer Ratio vs. Forward Current (non-sat.)




Fig. 15 - Switching Time vs. Load Resistance




Fig. 13 - Cut-Off Frequency vs. Collector Current




Fig. 16 - Voltage Gain vs. Frequency













Fig. 14 - Phase Angle vs. Frequency




### PACKAGE DIMENSIONS (in millimeters)



**SMD**




i178029



18450-11



# PACKAGE MARKING (example of SFH618A-3X001)




## Notes

- VDE logo is only marked on option 1 parts
- Tape and reel suffix (T) is not part of the package marking


## TAPE AND REEL PACKAGING (in millimeters)

The tape is 16 mm and is wound on a 33 cm reel. There are 1000 parts per reel. Taped and reeled 4 pin optocouplers conform to EIA-481-2 and IEC60286-3.

## SMD-4 ("T")




## SMD-4, 90° Rotation ("T1")






## SOLDER PROFILES



948626

Fig. 17 - Recommended Wave Soldering Double Wave Profile for DIP Devices



19841

Fig. 18 - Recommended Lead (Pb)-free Reflow Solder Profile for SMD Devices

## HANDLING AND STORAGE CONDITIONS

ESD level: HBM class 2

Floor life: unlimited

Conditions:  $T_{amb} < 30\text{ °C}$ , RH < 85 %

Moisture sensitivity level 1, according to J-STD-020



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.