

SMS18 Series Datasheet



Product Name:	Material:	Adhesive:
SMS18 Series	PET	Acrylic
Size:	Color:	Peeling-off Force:
8mm, 12mm, 16mm, 24mm, 32mm, 44mm, 56mm, 72mm, 88mm	Yellow, Black, Blue, Green, Pink, Etc Are Available	(N/25mm) By Angle Of 180 Degree ≥ 15

series double-sided positioning splicing tape, suitable for all specifications (8/12/16/24/32/44/56/72/88mm)

18 series double-sided splicing tape, suitable for joint carrier tapes in SMT process. which is composed of two adhesive tapes, release paper and removable PET with good adhesion.

Features And Benefits:

1. Edge&dots positioning, more accurate splicing.
2. Easy to operate, one piece to complete the jointing without splicing tools.
3. Universal type with wide range of applications (except for machines with induction).

Application:

used in the SMT process, for connection of various carrier tapes during SMT patching.

Properties:

Carrier Tape Size	Color	ESD	NO ESD
8mm/12mm/16mm/24mm/32mm/44mm	C	√	√
	B		√
	G	√	√
	M	√	√
	L	√	

Storage condition:

Temperature :20°C-30°C

Relative Humidity(RH):45%-65%

Shelf-life: One year

Keywords: SMT universal splice tape, SMT double-sided splice tape, SMT anti-static splice tape**Notes:**

Please be advised that this technical data sheet is written based on our lab tests and experience only. Customer is responsible to determine the suitability of the product meets intended application requirements before approved for use.