



Material: UL NYLON 66/PC
 (natural color/black) Fire rating
 94V-2

Product usage: PCB , plate , Good
 for computer or electronics
 equipment fixation
 Characteristic: For better
 insulation, light weight. No rust

Item No.				A	B	C	D	Pitch	Packing
PC		Nylon							
Natural color	Black	Natural color	Black						
PC-M2-05N	PC-M2-05NB	PF-M2-05	PF-M2-05B	2.0	05	1.4	3.5	0.4	
PC-M2-06N	PC-M2-06NB	PF-M2-06	PF-M2-06B		06				
PC-M2-08N	PC-M2-08NB	PF-M2-08	PF-M2-08B		08				
PC-M2-10N	PC-M2-10NB	PF-M2-10	PF-M2-10B		10				
PC-M2.5-06N	PC-M2.5-06NB	PF-M2.5-06	PF-M2.5-06B	2.5	06	2.0	4.5	0.45	
PC-M2.5-08N	PC-M2.5-08NB	PF-M2.5-08	PF-M2.5-08B		08				
PC-M2.5-10N	PC-M2.5-10NB	PF-M2.5-10	PF-M2.5-10B		10				
PC-M3.0-04N	PC-M3.0-04NB	PF-M3.0-04	PF-M3.0-04B	3.0	04	2.5	5.6	0.5	
PC-M3.0-06N	PC-M3.0-06NB	PF-M3.0-06	PF-M3.0-06B		06				
PC-M3.0-08N	PC-M3.0-08NB	PF-M3.0-08	PF-M3.0-08B		08				
PC-M3.0-10N	PC-M3.0-10NB	PF-M3.0-10	PF-M3.0-10B		10				
PC-M3.0-12N	PC-M3.0-12NB	PF-M3.0-12	PF-M3.0-12B		12				
PC-M3.0-15N	PC-M3.0-15NB	PF-M3.0-15	PF-M3.0-15B		15				

GENERAL TOLERANCE	PROJECTION		Description:
X. ±0.50	UNITS	mm	Pan Head Screws
.X ±0.25	SCALE	1:1	
.XX ±0.10	Draw by:	Jenny	
ANGLE TOLERANCE	Check by:		KLS P/N: L-KLS8-0318-PF-M2-05
X. ±5°	Date	2018-03-01	NingBo KLS ELECTRONIC CO.,L TD.
.X ±3°	SHEET	1 OF 1	
.XX ±2°			