



Representative Image

Ref. No. 112166 | Cat. No. CL10E300MD

Description: CL10E300MD Contactor 3-pole 24V 50/60Hz

EAN 8425095121669

Home > Power devices > Contactors > 4. Series CL: Contactor for general purpose application 9-105A AC3

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 24V 50/60Hz Max.oper.current AC1 (A):140Max.oper.current AC3 (A):105 Admissible power 220V/230V (kW):30 Admissible power 380V/400V (kW):55

Descriptors

Category	4. Series CL: Contactor for general purpose application 9-105A AC3
----------	--

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC/DC
Terminal type	Double clamp terminal
Max. operating current AC1 Non-inductive loads	140 A
Max. operating current AC3 Motors = 480V, 3-phase 50/60Hz	105 A
Electrical endurance: # operations AC3	1.5 x 10 ⁶
Type	Coil with electronic module for contactors CL - E
Admissible power AC3 220V, 230V	30 kW
Admissible power AC3 380V, 400V	55 kW
Admissible power AC3 415V, 440V	55 kW
Admissible power AC3 500V	65 kW
Package (pcs)	1
Class	1. Contactors

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	1.460 kg
--------	----------