



Representative Image

Ref. No. 112176 | Cat. No. CL01D400TD
Description: CL01D400TD Contactor 4-pole 24V DC
EAN 8017018121766
Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application

Series CL & RL, 4-pole contactor, Terminal: screw, Control Voltage (V): 24 V DC Max.oper.current AC1 (A): 25 Max.oper.current AC3 (A): 12 Admissible power 220V/230V (kW): 9,5 Admissible power 380V/400V (kW): 16,5 Aux.contacts: -

Descriptors

Category	Series CL - Contactor series for General Purpose application
----------	--

Specifications

Series	Four-pole contactors from 25 to 140 A (AC1)
Control circuit	DC
Control Voltage: DC	24 V
Terminal type	Screw terminal
Non-inductive loads AC1	25 A
Motors = 440V, 3-phase 50/60Hz AC3	12 A
Electrical endurance: # operations AC1	1.5 x 10 ⁶
Power contacts	4NO
Type	For contactors type CL - D
Admissible power AC1 220V, 230V	9.5 kW
Admissible power AC1 380V, 400V	16.5 kW
Admissible power AC1 415V, 440V	18 kW
Admissible power AC1 500V	21.5 kW
Package (pcs)	10

Classifications

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

Dimensions

Weight	0.490 kg
--------	----------

Publications

Title	Publication No.	Publication Type
Auxiliary contactor RL4RD (stp)		
Auxiliary contactor RL4RD (STEP format)	3D-00016	Drawings - CAD - 3D
Auxiliary contactor RL4RD (pdf)		
Auxiliary contactor RL4RD (3DPDF format)	3D-00016-PDF	Drawings - CAD - 3D

Additional Documentation: Visit our Publication Library to find technical documentation, specifications, articles, promotional literature, 3D's,...