



Ref. No. 110676 | Cat. No. CL03AB00M5

Description: Double clamp terminal 4P, AC3 12kW 380-400V, 220V/50-60Hz AC Bifreq. coil (GE)

EAN 8425095106765

Products > Power devices > Contactors > Series CL - Contactor series for General Purpose application

- Power circuit (AC): Up to 690V
- Control circuit:
Alternating current up to 690V AC
- Direct current up to 440V DC
- Terminal numbering in accordance with EN50005 and EN 50012
- Fixing by clipping onto 35mm DIN rail EN50022-35 or by screws
- Degree of protection IP20
- screws protected against accidental contact in accordance with VDE 0106
- Three coil terminals
- The types CL...E are also suitable for AC controls
- Accessories:
Mounting possibilities of front/side instantaneous auxiliary contact blocks, timed auxiliary contact blocks, mechanical latch, transient suppressor block and interface modules
- Maximum number of auxiliary contacts: 4

Descriptors

Category | Series CL - Contactor series for General Purpose application

Specifications

Series	Four-pole contactors from 12 to 80 A (AC3) [2NO+2NC]
Control circuit	AC
Control Voltage: AC Bifreq. Coil (at 50-60 Hz)	220 V
Terminal type	Double clamp terminal
Non-inductive loads AC1	45 A
Motors = 440V, 3-phase 50/60Hz AC3	25 A
Power contacts	2NO+2NC
Control Voltage: AC Bifreq. Coil (at 50-60 Hz)	220 V
Admissible power AC3 220V, 230V	7,5 kW
Admissible power AC3 380V, 400V	12 kW
Admissible power AC3 415V, 440V	12 kW
Admissible power AC3 500V	15 kW
Package (pcs)	10

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	0.490 kg
--------	----------

Publications

Title	Publication No.	Publication Type
CONACL03L CONACL03 Side view	CONACL03L	Commercial Drawings
CONACL03T CONACL03 Total view	CONACL03T	Commercial Drawings
CONACL03R CONACL03 Rear view	CONACL03R	Commercial Drawings
CONACL03F CONACL03 Front view	CONACL03F	Commercial Drawings

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...