



Representative Image

**Ref. No. 109244 | Cat. No. CL01A310T1**

**Description: CL01A310T1 Contactor SLA Plus 3-pole 24V 50/60Hz**

**EAN 8017018092448**

**Products > Power devices > Contactors > Series CL - Contactor series for General Purpose application**

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 24 VAC Max.oper.current AC1 (A): 25 Max.oper.current AC3 (A): 12 Admissible power 220V/230V (kW): 3 Admissible power 380V/400V (kW): 5,5 Aux.contacts: 1NO

**Descriptors**

Category | Series CL - Contactor series for General Purpose application

**Specifications**

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Terminal type	Screw terminal
Non-inductive loads AC1	25 A
Motors = 440V, 3-phase 50/60Hz AC3	12 A
Electrical endurance: # operations AC3	2 x 10 <sup>6</sup>
Aux Contacts	1NO
Type	For contactors type CL - D
Control Voltage: AC	24 V
Admissible power AC3 220V, 230V	3 kW
Admissible power AC3 380V, 400V	5.5 kW
Admissible power AC3 415V, 440V	5.5 kW
Admissible power AC3 500V	7.5 kW
Package (pcs)	5

**Classifications**

ETIM 5.0	EC000066
ETIM 6.0	EC000066

**Dimensions**

Weight	0.295 kg
--------	----------

## Publications

Title	Publication No.	Publication Type
<a href="#">Auxiliary contactor RL4RA (pdf)</a>		
Auxiliary contactor RL4RA (3DPDF format)	3D-00015-PDF	Drawings - CAD - 3D
<a href="#">Auxiliary contactor RL4RA (stp)</a>		
Auxiliary contactor RL4RA (STEP format)	3D-00015	Drawings - CAD - 3D

**Additional Documentation:** Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...