



Representative Image

**Ref. No. 109346 | Cat. No. CL02A301T6**
**Description: CL02A301T6 Contactor SLA Plus 3-pole 230V 50/60Hz**
**EAN 8017018093469**
**Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application**

Series CL &amp; RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 230 VAC Max.oper.current AC1 (A): 32 Max.oper.current AC3 (A): 18 Admissible power 220V/230V (kW): 4 Admissible power 380V/400V (kW): 7,5 Aux.contacts: 1NC

**Descriptors**

Category	Series CL - Contactor series for General Purpose application
----------	--

**Specifications**

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Terminal type	Screw terminal
Non-inductive loads AC1	32 A
Motors = 440V, 3-phase 50/60Hz AC3	18 A
Electrical endurance: # operations AC3	1.7 x 10 <sup>6</sup>
Aux Contacts	1NC
Type	For contactors type CL - D
Control Voltage: AC	220-230 V
Admissible power AC3 220V, 230V	4 kW
Admissible power AC3 380V, 400V	7.5 kW
Admissible power AC3 415V, 440V	7.5 kW
Admissible power AC3 500V	10 kW
Package (pcs)	5

**Classifications**

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

**Dimensions**

Weight	0.295 kg
--------	----------

## Publications

Title	Publication No.	Publication Type
<a href="#">Auxiliary contactor RL4RA (pdf)</a>		
Auxiliary contactor RL4RA (3DPDF format)	3D-00015-PDF	Drawings - CAD - 3D
<a href="#">Auxiliary contactor RL4RA (stp)</a>		
Auxiliary contactor RL4RA (STEP format)	3D-00015	Drawings - CAD - 3D

**Additional Documentation:** Visit our Publication Library to find technical documentation, specifications, articles, promotional literature, 3D's,...