



Representative Image

**Ref. No. 104054 | Cat. No. CL00A310TN**

**Description: CL00A310TN Contactor 3-pole 220-230V 50Hz / 277V 60Hz AC**

**EAN 8017018040548**

**Products > Power devices > Contactors > Series CL - Contactor series for General Purpose application**

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 220-230V 50Hz/277V 60Hz  
 Max.oper.current AC1 (A): 25 Max.oper.current AC3 (A): 9 Admissible power 220V/230V (kW): 2,2 Admissible power 380V/400V (kW): 4 Aux.contacts: 1NO

**Descriptors**

Category | Series CL - Contactor series for General Purpose application

**Specifications**

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Terminal type	Screw terminal
Non-inductive loads AC1	25 A
Motors = 440V, 3-phase 50/60Hz AC3	9 A
Electrical endurance: # operations AC3	2 x 10 <sup>6</sup>
Aux Contacts	1NO
Control Voltage: AC	220-230 V / 277 V
Admissible power AC3 220V, 230V	2.2 kW
Admissible power AC3 380V, 400V	4 kW
Admissible power AC3 415V, 440V	4 kW
Admissible power AC3 500V	5.5 kW
Package (pcs)	5
Frequency Coil voltages: alternating current	50 Hz / 60 Hz

**Classifications**

ETIM 5.0	EC000066
ETIM 6.0	EC000066

**Dimensions**

Weight	0.295 kg
--------	----------

## Publications

Title	Publication No.	Publication Type
<a href="#">CONACL00L</a> CONACL00 Side view	CONACL00L	Commercial Drawings
<a href="#">CONACL00T</a> CONACL00 Total view	CONACL00T	Commercial Drawings
<a href="#">Auxiliary contactor RL4RA (stp)</a> Auxiliary contactor RL4RA (STEP format)	3D-00015	Drawings - CAD - 3D
<a href="#">CONACL00F</a> CONACL00 Front view	CONACL00F	Commercial Drawings
<a href="#">Auxiliary contactor RL4RA (pdf)</a> Auxiliary contactor RL4RA (3DPDF format)	3D-00015-PDF	Drawings - CAD - 3D
<a href="#">CONACL00R</a> CONACL00 Rear view	CONACL00R	Commercial Drawings

**Additional Documentation:** Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...