



Representative Image

Ref. No. 109608 | Cat. No. CL07A300M5

Description: CL07A300M5 Contactor 3-pole 220V 50-60Hz AC

EAN 8425095096080

Products > Power devices > Contactors > Series CL - Contactor series for General Purpose application

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 220V 50-60Hz AC
 Max.oper.current AC1 (A):110Max.oper.current AC3 (A):65 Admissible power 220V/230V (kW):18.5 Admissible power 380V/400V (kW):30

Descriptors

Category | Series CL - Contactor series for General Purpose application

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Terminal type	Double clamp terminal
Non-inductive loads AC1	110 A
Motors = 440V, 3-phase 50/60Hz AC3	65 A
Electrical endurance: # operations AC3	1.7 x 10 ⁶
Type	For contactors type CL - D
Control Voltage: AC	220 V
Admissible power AC3 220V, 230V	18,5 kW
Admissible power AC3 380V, 400V	30 kW
Admissible power AC3 415V, 440V	37 kW
Admissible power AC3 500V	40 kW
Package (pcs)	10

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	1.090 kg
--------	----------