



Ref. No. 102621 | Cat. No. MC1A310AT5

Description: Screw terminal 3P, AC3 4kW, 220V/50-60Hz AC Bifreq. Coil, 1NO (GE)

EAN 8425095026216

Products > Power devices > Contactors > Series M - Compact contactor series up to 12A

- Control circuit:
Alternating current up to 600V
Direct current up to 250V
- Terminal numbering in accordance with EN 50012
- Fixing by clipping onto 35mm DIN rail (EN 50022) or by screws
- Degree of protection IP20 in accordance with EN 60529
- Printed circuit version available
- Screws and fast-on terminals protected against accidental contact in accordance with VDE 0106 T.100 and VBG4
- Facility to mount instant and timed auxiliary contact blocks and voltage suppressor block
- Conform to IEC/EN60947-1, IEC/EN60947-4-1, IEC/EN60947-5-1

Descriptors

Category	Series M - Compact contactor series up to 12A
----------	---

Specifications

Series	Three-pole contactors 6, 9 and 12 A (AC3)
Control circuit	AC
Terminal	Screw terminal
Non-inductive load AC1	20 A
Aux Contacts	1NO
Control Voltage: AC Bifreq. Coil (at 50-60 Hz)	220 V
Motors = 440V, 3-phase 50/60Hz AC3	9 A
Admissible Power AC3 1-Phase 115V	0,56 kW
Admissible Power AC3 1-Phase 220V, 230V	1,1 kW
Admissible Power AC3 3-Phase 220V, 230V	3 kW
Admissible Power AC3 3-Phase 380V, 400V	4 kW
Admissible Power AC3 3-Phase 500V	4 kW
Package (pcs)	20

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	0.170 kg
--------	----------