

Ref. No. 103577 | Cat. No. MC2A310AT1
Description: Screw terminal 3P, AC3 5.5kW, 24V/50-60Hz AC Bifreq. Coil, 1NO (GE)
EAN 8425095035775
Home > Power devices > Contactors > Series M - Compact contactor series up to 12A

- Control circuit:
Alternating current up to 600V
Direct current up to 250V
- Terminal numbering in accordance with EN 50005
- Fixing by clipping onto 35mm DIN rail (EN 50022) or by screws
- Degree of protection IP20 in accordance with EN 60529
- Screws and fast-on terminals protected against accidental contact in accordance with VDE 0106 T.100 and VBG4
- Facility to mount instant and timed auxiliary contact blocks and voltage suppressor block
- Printed circuit version available
- Conform to IEC/EN60947-1, IEC/EN60947-4-1, IEC/EN60947-5-1



Representative Image

Descriptors

Category	Series M - Compact contactor series up to 12A
----------	---

Specifications

Series	Three-pole contactors 6, 9 and 12 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Control Voltage: AC	24 V
Terminal	Screw terminal
Aux Contacts	1NO
Motors = 440V, 3-phase 50/60Hz AC3	12 A
Package (pcs)	20

Classifications

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

Dimensions

Weight	0.170 kg
--------	----------