



Representative Image

Ref. No. 109490 | Cat. No. CL04A301M6
Description: CL04A301M6 Contactor 3-pole 230V 50/60Hz
EAN 8425095094901
Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 230 VAC Max.oper.current AC1 (A): 60 Max.oper.current AC3 (A): 32 Admissible power 220V/230V (kW): 9 Admissible power 380V/400V (kW): 16 Aux.contacts: 1NC

Descriptors

Category	Series CL - Contactor series for General Purpose application
----------	--

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Terminal type	Double clamp terminal
Non-inductive loads AC1	60 A
Motors = 440V, 3-phase 50/60Hz AC3	32 A
Electrical endurance: # operations AC3	2 x 10 ⁶
Aux Contacts	1NC
Type	For contactors type CL - D
Control Voltage: AC	220-230 V
Admissible power AC3 220V, 230V	9 kW
Admissible power AC3 380V, 400V	16 kW
Admissible power AC3 415V, 440V	16 kW
Admissible power AC3 500V	18.5 kW
Package (pcs)	10

Classifications

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

Dimensions

Weight	0.520 kg
--------	----------

Publications

Title	Publication No.	Publication Type
4-pole CL03A-CL04A (pdf)		
4-pole CL03A-CL04A (3DPDF format)	3D-00017-PDF	Drawings - CAD - 3D
4-pole CL03A-CL04A (stp)		
4-pole CL03A-CL04A (STEP format)	3D-00017	Drawings - CAD - 3D

Additional Documentation: Visit our Publication Library to find technical documentation, specifications, articles, promotional literature, 3D's,...