



Representative Image

Ref. No. 110728 | Cat. No. CL25A300T1

Description: CL25A300T1 Contactor SLA Plus 3-pole 24V 50/60Hz

EAN 8017018107289

Products > Power devices > Contactors > Series CL - Contactor series for General Purpose application

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 24 VAC Max.oper.current AC1 (A): 45 Max.oper.current AC3 (A): 25 Admissible power 220V/230V (kW): 7,5 Admissible power 380V/400V (kW): 11 Aux.contacts: -

Descriptors

Category | Series CL - Contactor series for General Purpose application

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Terminal type	Screw terminal
Non-inductive loads AC1	45 A
Motors = 440V, 3-phase 50/60Hz AC3	25 A
Electrical endurance: # operations AC3	2 x 10 ⁶
Type	For contactors type CL - D
Control Voltage: AC	24 V
Admissible power AC3 220V, 230V	7,5 kW
Admissible power AC3 380V, 400V	11 kW
Admissible power AC3 415V, 440V	11 kW
Admissible power AC3 500V	15 kW
Package (pcs)	5

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	0.270 kg
--------	----------

Publications

Title	Publication No.	Publication Type
CONACL25R CONACL25 Rear view	CONACL25R	Commercial Drawings
CONACL25L CONACL25 Side view	CONACL25L	Commercial Drawings
CONACL25T CONACL25 Total view	CONACL25T	Commercial Drawings
CONACL25F CONACL25 Front view	CONACL25F	Commercial Drawings
Series CL - Contactor 3-pole CL25A (stp) 3D Drawing: Controls - Series CL - Contactor 3-pole CL25A (STEP format)	3D-00031	Drawings - CAD - 3D
Series CL - Contactor 3-pole CL25A (pdf) 3D PDF Viewer: Controls - Series CL - Contactor 3-pole CL25A (3DPDF format)	3D-00031-PDF	Drawings - CAD - 3D

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...