

Ref. No. 101268 | Cat. No. GPS1MSAM
Description: MANUAL MOTOR STARTER MAG.PROT. GPS1 16A STAND.BREAKING
EAN 4538915012680
Home > Power devices > Manual Motor Starters > Manual motor starter - SURION

Descriptors

Category	Manual motor starter - SURION
----------	-------------------------------

Specifications

Series	Surion - GPS1M - Magnetic protection (Ie max 32A)
Rated power 3 phase motors at 220/230Vac Pn (kW)	3.7/4 kW
Rated power 3 phase motors at 400Vac Pn (kW)	7.5 kW
Rated power 3 phase motors at 440Vac Pn (kW)	7.5 kW
Rated power 3 phase motors at 500/525Vac Pn (kW)	10 kW
Rated power 3 phase motors at 660/690Vac Pn (kW)	11 kW
Rated current (A)	16 A
Capacity	GPS1MS - Standard breaking capacity
Instantaneous short-circuit release (A)	208 A
Rated ultimate short-circuit breaking cap 220/230V Icu kA	100 kA
Rated ultimate short-circuit breaking cap 400V Icu kA	25 kA
Rated ultimate short-circuit breaking cap 440V Icu kA	35 kA
Rated ultimate short-circuit breaking cap 500/525V Icu kA	10 kA
Rated ultimate short-circuit breaking cap 600V Icu kA	4 kA
Rated ultimate short-circuit breaking cap 690V Icu kA	4 kA
Rated service short-circuit breaking cap 220/230V Ics kA	100 kA
Rated service short-circuit breaking cap 400V Ics kA	19 kA
Rated service short-circuit breaking cap 440V Ics kA	8 kA
Rated service short-circuit breaking cap 500/525V Ics kA	5 kA
Rated service short-circuit breaking cap 600V Ics kA	3 kA
Rated service short-circuit breaking cap 690V Ics kA	3 kA
Pack	5

Classifications

ETIM 5.0	EC000074 - Motor protection circuit-breaker
ETIM 6.0	EC000074 - Motor protection circuit-breaker
ETIM 7.0	EC000074 - Motor protection circuit-breaker

Dimensions

Weight

0.280 kg