



## Button Type



Model	Nominal Voltage (V)	Nominal Capacity(mAh)		Recommended continuous current (mA)	Recommended pulse current (mA)	Dimension (mm)		Approx. Weight (g)	
		Typical	Minimum			Diameter	Height		
LIR1025	3.6	6±1		0.2C	0.5C	10.0	2.5	0.6±0.2	
LIR1220	3.6	7±1				12.5	2.0	0.8±0.2	
LIR1255	3.6	55±5				12.5	5.5	1.85±0.2	
LIR1620	3.6	15±2				16.0	2.0	1.2±0.2	
LIR1632	3.6	25±2				16.0	3.2	1.7±0.2	
LIR1655	3.6	100±10				16.1	5.5	3.0±0.2	
LIR2016	3.6	15±2				20.0	1.6	1.7±0.2	
LIR2025	3.6	30±2				20.0	2.5	2.3±0.2	
LIR2032	3.6	40±2				20.0	3.2	2.8±0.3	
LIR2430	3.6	55±5			24.5	3.0	3.8±0.3		
LIR2440	3.6	80±5			24.5	4.0	4.4±0.3		
LIR2450	3.6	120±10			24.5	5.0	5.3±0.3		
LIR2466	3.6	145±5			24.5	6.6	6.7±0.3		
LIR2477	3.6	185±5			24.5	7.7	7.5±0.3		
LIR3032	3.6	180±10			30.0	3.2	7.3±0.3		
LIR3048	3.6	280±10			30.0	4.8	9.3±0.3		
<b>High Capacity Version</b>									
LIR1220H	3.6	11±1			0.2C	0.5C	12.5	2.0	0.8
LIR1620H	3.6	20±2		16.0			2.0	1.3	
LIR1632H	3.6	32±2		16.0			3.2	1.7	
LIR2016H	3.6	28±2		20			1.6	1.8	
LIR2025H	3.6	36±2		20			2.5	2.6	
LIR2032H	3.6	70±2		20		3.2	3.0		
LIR2235H	3.6	80±5		22		3.5	3.7		
LIR2430H	3.6	78±5		24.5		3.0	4.2		
LIR2440H	3.6	138±5		24.5		4.0	<b>5.4</b>		
LIR2450H	3.6	200±10		24.5		5.0	6.4		

Operation Temperature:-20 ~ +60°C