


USL120070-2


12V7AH

3-5 YEARS DESIGN LIFE

Constant voltage charging characteristics



Float Life



Constant Current Discharge Characteristics (A, 25°C)

F.V/Time	5min	10min	15min	30min	60min	2h	3h	5h	8h	10h	20h
9.60V	24.30	16.20	12.60	6.60	4.23	2.24	1.56	1.06	0.73	0.64	0.33
10.2V	22.20	15.10	11.80	6.50	4.10	2.18	1.53	1.04	0.71	0.63	0.33
10.5V	19.80	14.20	11.30	6.40	3.96	2.16	1.51	1.02	0.70	0.62	0.32
10.8V	18.50	10.80	10.80	6.20	3.91	2.13	1.49	1.00	0.69	0.61	0.32

Constant Current Discharge Characteristics (Watt, 25°C)

F.V/Time	5min	10min	15min	30min	60min	2h	3h	5h	8h	10h	20h
9.60V	262.50	176.60	138.60	73.92	48.20	25.80	18.10	12.40	8.60	7.60	3.93
10.2V	244.20	167.60	132.20	73.45	46.70	25.10	17.80	12.20	8.40	7.50	3.90
10.5V	219.80	159.20	127.70	72.96	45.50	25.30	17.60	12.10	8.40	7.40	3.80
10.8V	207.20	122.10	123.10	71.30	44.90	24.90	17.40	11.80	8.20	7.30	3.75

Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
Battery	12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%

★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.