

ULL1201000-2


12V100AH

10 YEARS DESIGN LIFE



Plane Chart:


Unit:(mm) Terminal type:(T3)




Parameter Chart:

Volts		12V
Capacity(25°C)	10 hours rate (10A)	100Ah
Discharge Current Testing (25°C)	1 hours rate (55A)	55Ah
	3 hours rate (25A)	75Ah
Internal Resistance	Full Charged Battery 25°C	5.5mΩ
Capacity Affected By Temperature	40°C	104%
	25°C	100%
	0°C	83%
	-15°C	65%
Residual Capacity (25°C)	Capacity After 3 Months Storage	91%
	Capacity After 6 Months Storage	82%
	Capacity After 12 Months Storage	65%
Charge (Constant Voltage)	Cycle (25°C)	Initial Charging Current Less Than 30A Voltage 14.5~14.9V
	Float (25°C)	Charge Voltage 13.6~13.8V
Weight (Approx)		28.1Kg

Residual Capacity



Discharge Current 25°C




★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.

ULL1201000-2


12V100AH

10 YEARS DESIGN LIFE

Constant voltage charging characteristics



Float Life



Constant Current Discharge Characteristics(A,25°C)

F.V/Time	10min	15min	30min	60min	2h	3h	5h	8h	10h	20h
9.60V	193.8	160.2	97.4	54.5	33.1	24.1	17.1	11.2	9.6	5.1
10.2V	182.5	156.5	94.2	53.6	32.4	23.7	17.0	11.0	9.6	5.1
10.5V	171.6	152.6	92.5	52.2	31.7	23.4	16.8	10.8	9.5	5.0
10.8V	158.9	142.6	90.3	50.7	30.5	23.0	16.4	10.6	9.5	4.9

Constant Power Discharge Characteristice(Watt,25°C)

F.V/Time	10min	15min	30min	60min	2h	3h	5h	8h	10h	20h
9.60V	2093.0	1762.2	1115.6	625.6	375.6	278.9	197.5	129.5	110.2	59.5
10.2V	2007.5	1721.5	1085.2	617.5	370.2	273.6	194.2	127.4	109.5	58.4
10.5V	1921.9	1678.6	1067.5	606.2	363.6	268.5	191.6	125.2	108.2	57.6
10.8V	1779.7	1597.1	1046.3	589.1	351.7	262.4	188.5	120.6	107.1	56.6

Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
Battery	12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%

★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.