



Designation IEC:

HR03

Size:.....	AAA
Nominal Voltage:.....	1.2 V
Rated Capacity:.....	1000 mAh
Internal Resistance DC; fully charged:.....	80 mΩ
Impedance AC at 1 kHz; fully charged:.....	40 mΩ
Max. Discharge Current (continuous load / 0.8 V):.....	2.0 A

Typical Capacity at:

0.2 C / 1.0 V:.....	1000 mAh
1.0 C / 0.9 V:.....	900 mAh

Charge Retention:

65 % of initial capacity after one year storage at 20 °C;
determined at 0.2 C discharge rate

Dimensions:

Diameter	a:.....	10.5^{-1.0} mm
Height	b:.....	44.5^{-1.2} mm
Shoulder Height	c:.....	43.7^{-1.2} mm
Cap Diameter	d:.....	3.8^{-1.8} mm
Volume:.....		3.8 cm³
Weight (approx.):.....		14 g

Charge Conditions at:

Standard Charge:.....	100 mA, 16 h
Fast Charge:.....	1000 mA (-dV)
Trickle Charge (0.03 - 0.05 C):.....	30 - 50 mA

Temperatures (recommended / permissible) at:

Storage:.....	-20 °C ... 25 °C / -20 °C ... 40 °C
Charge:.....	15 °C ... 30 °C / 0 °C ... 45 °C
Fast Charge:.....	15 °C ... 30 °C / 0 °C ... 40 °C
Discharge:.....	0 °C ... 40 °C / 0 °C ... 50 °C

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries