

**Din Plug Connector** KLS1-295

**Din Plug Connector:**

**How to order Example:**

KLS1-295-M-7-B  
 M-MALE F-FEMALE  
 7=7 PIN Or 3PIN 4PIN 5PIN 6PIN 8PIN  
 B=BLACK

**MATERIAL:**

COVER : PE 2L  
 SHELL : ABS  
 METAL SHIELD : BRASS NICKEL PLATED  
 HOUSING : NYLON66 GF  
 CONTACT: BRASS SILVER PLATED

**SPECIFICATIONS:**

RATING : 100V AC 1A MAX OR 12V DC 2A MAX.  
 INSULATION RESISTANCE : 50M OHM MIN AT 500V DC.  
 DIELECTRIC STRENGTH : 500V AC / 1 MINUTE.

Material:  
 Insulator: High temperature thermoplastic with g.f,UL94v-0  
 Contact: Copper alloy,t=0.60mm  
 Shell: Spcc,t=0.40mm

Specification:  
 Current rating: 1 A Max.  
 Dielectric withstanding voltage: 750 V(ac) for 1 min.  
 Contact resistance: 30 mΩ Max.  
 Insulation resistance: 1000 MΩ Min.  
 Total mating force: 5.5 Kgf Max.  
 Total unmating force: 1.0 Kgf Min.  
 Temperature range: -55°C~85°C

NO.OF CONTACT	3(180°)	4(210°)	5(180°)	6(240°)	7(270°)	8(270°)
PART NO.	DA-S-03	DA-S-04	DA-S-05	DA-S-06	DA-S-07	DA-S-08
POSITION						

