


SCHMATIC



- SPECIFICATION**  
 1. Rating : DC 30V 0.5A ;  
 2. Contact resistance :  $\leq 0.03\Omega$  ;  
 3. Insulation resistance :  $\geq 100M\Omega$  (DC250V) ;  
 4. Withstand voltage : 500VAC ;  
 5. Insertion and extraction force : 3-25N ;  
 6. life test : 5,000 cycles .

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
6	COVER	1	PA66/PBT	
5	HOUSING	1	PA66/PBT	
4	AXIS SUPPORT	1	H59 BRASS	Ni-Plating
3	CURVE PIECE	1	H62 BRASS	Cu-Sn-Plating
2	SPRING PIECE	1	65Mn STEEL	Sn-Sb-Plating
1	FLAT PIECE	1	H62 BRASS	Cu-Sn-Plating

UNIT:MM 	TYPE: PHONE JACK	MODEL NO: L-KLS1-TSJ3.5-008F	PAPER NO:	PAGE 1 OF 1	
			TOLERANCE	ANGLES	SCALE
			$\pm 0.15$	$\pm 1.5^\circ$	4:1 1

DESIGNER		<b>KLS ELECTRONIC CO., LTD</b>
CHECK		
APPROVED BY:		