

Hinged frame 24B for 6 modules (A..F)



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 14 024 0303 |
| Specification | Hinged frame 24B for 6 modules (A..F) |
| HARTING eCatalogue | https://b2b.harting.com/09140240303 |

Identification

| | |
|------------------------------|--|
| Category | Accessories |
| Series | Han-Modular® |
| Type of accessory | Hinged frame |
| Description of the accessory | for 6 modules A ... F |
| Features | Conductor cross-section PE (power side) 4 ... 10 mm ² Conductor cross-section PE (signal side) 1 ... 2.5 mm ² |

Version

| | |
|------|------|
| Size | 24 B |
|------|------|

Technical characteristics

| | |
|----------------------|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥500 |

Material properties

| | |
|-----------------------------|--|
| Material | Zinc die-cast |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |



Pushing Performance

Material properties

| | |
|--------------------------------------|--------------------------------------|
| REACH SVHC substances | Lead |
| ECHA SCIP number | 564b7d75-7bf6-4cfb-acb1-2168eb61b675 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel Lead |

Specifications and approvals

| | |
|----------------|-------------------------|
| Specifications | EN 60664-1 IEC 61984 |
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 2 |
| Net weight | 76.1 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440206 Module carrier frame for industrial connectors |