

REVISION RECORD			
REV	ECN	DESCRIPTION	DRFT

Technical characteristics:

Specifications

DIN EN 60 664

DIN EN 61 984

Inserts

01. Number of contacts :2

02. Rated Current :70A

03. Rated Voltage :1000V

04. Pollution degree :3

05. Rated impulse voltage :8kv¹⁰06. Insulation resistance : $\geq 10 \Omega$

07. Material:Polycarbonate

08. Rated voltage acc. to UL:600V

09. Limiting temperatures : $-40^{\circ}\text{C}\sim+125^{\circ}\text{C}$

10. Flammability acc. to UL94:V0

11. Mechanical working life

(mating cycles) : ≥ 500

Contacts

01. Material:Copper alloy

02. Surface:hard-silver plated

03. Contact resistance :0.5m Ω

04. Terminal :Axial screw terminal





05. Wire gauge :14-22mm²

06. Hexagonal driver:SW2.5

07. Stripping length :11mm

08. Tightening torque :2-4Nm

09. Rohs Compliance



PART NO: /		宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
APPD: HYS 2016.8.26	NAME: DMK7-002-M(14-22mm ²)		
CHKD: Ljm 2016.9.25	TITLE: CUSTOMER DRAWING		
DRFT: yang 2016.08.22	REV DO-1		
THIRD ANGLE PROJECTION		DRAWING NO: 1/1 DO NOT SCALE DRAWING SCALE	