



Technical characteristics:

Specifications

DIN EN 60 664-1
DIN EN 61 984

Inserts

- 01. Number of contacts :40+PE
- 02. Rated Current :10A
- 03. Rated Voltage :250V
- 04. Pollution degree :3
- 05. Rated impulse voltage :4kv
- 06. Insulation resistance :≥10Ω
- 07. Material:Polycarbonate
- 08. Rated voltage acc.to UL/CSA:600V
- 09. Limiting temperatures :-40℃~+125℃
- 10. Flammability acc.to UL94:V0
- 11. Mechanical working life (mating cycles) :≥500

Contacts

- 01. Material:Copper alloy
- 02. Surface:hard-silver plated
- 03. Contact resistance :≤3mΩ
- 04. Terminal :Crimp terminal
- 05. Wire gauge :0.14-2.5mm² (AWG 26-14)
- 06. Stripping length :8.0mm
- 07. Rots Compliance

Note:Crimp contact pins should order separately

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE

PART NO: /		NINGBO DEGSON ELECTRICAL CO., LTD	
APPD: MJS 2016.8.25	NAME: 宁波高松电子有限公司		
CHKD: Ljm 2016.8.25	DD-040-MC		
DRFT: 2016.07.25	TITLE: CUSTOMER DRAWING		
THIRD ANGLE PROJECTION		REV	DO-1
MM (INCH)		DRAWING-NO.: DD-040-MC-E01	SHEET 1/1
DO NOT SCALE		DRAWING SCALE	