





REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE

Technical characteristics:
 Specifications
 DIN EN 60 664
 DIN EN 61 984

Inserts

01. Number of contacts :2
02. Rated Current :70A
03. Rated Voltage :1000V
04. Pollution degree :3
05. Rated impulse voltage :8kV¹⁰
06. Insulation resistance :≥10Ω
07. Material:Polycarbonate
08. Rated voltage acc. to UL:600V
09. Limiting temperatures :-40℃~+125℃
10. Flammability acc. to UL94:V0
11. Mechanical working life (mating cycles) :≥500

- Contacts
01. Material:Copper alloy
 02. Surface:hard-silver plated
 03. Contact resistance :0.5mΩ
 04. Terminal :Axial screw terminal
 05. Wire gauge :14-22mm²
 06. Hexagonal driver:SW2.5
 07. Stripping length :11mm
 08. Tightening torque :2-4Nm
 09. Rohs Compliance



DETACHED LISTS			
PART NO.:	/	NINGBO DEGSON ELECTRICAL CO., LTD	
APPD:		宁波高松电子有限公司	
CHKD:		DMK7-002-M(14-22mm ²)	
DRFT:	YONG	2016.08.22	TITLE: CUSTOMER DRAWING
			REV: DO-1
			SHEET: 1/1
			SCALE
			DO NOT SCALE DRAWING
			THIRD ANGLE PROJECTION

A 8 7 6 5 4 3 2 1