

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

COPYRIGHT - new logo 2011

ALL RIGHTS RESERVED.

LOC
HDIST
-

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	ECR-16-015010	24OCT2016	KR	MvE
	B	ECR-17-008373	16OCT2017	RK	PO

NOTES:

- CONNECTOR ACCEPTS MULTIPLE WIRES SIZES: SEE TABLE.
- HOUSING AND BUTTON MATERIAL : POLYCARBONATE
- IDC CONTACT MATERIAL: PhBR
- PRINTING LOGO'S: UL Listed Logo, KEMA, PARTNUMBER, TE, DATE CODE, WIRE SIZE, IP CLASS.
- WIRE INSULATION DIAMETER RANGE IS FROM 1.75 TO 2.85 mm

BLUE	CLEAR	2213800-4	△	SPLICING CONNECTOR SEALED	AWG 20 (0.52mm ²) / AWG 22 (0.33mm ²)
GREEN		2213800-3	△	SPLICING CONNECTOR UNSEALED	AWG 20 (0.52mm ²) / AWG 22 (0.33mm ²)
BLUE		2213800-2	△	SPLICING CONNECTOR SEALED	AWG 18 (0.82mm ²) TO 0.75mm ²
GREEN		2213800-1	△	SPLICING CONNECTOR UNSEALED	AWG 18 (0.82mm ²) TO 0.75mm ²
BUTTON COLOR	HOUSING COLOR	PARTNUMBER		DESCRIPTION	CABLE SIZE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 22DEC2015

RAGHAVENDRA.K

CHK 22DEC2015

M.V.ESEN

APVD 22DEC2015

O.L.F.J.NSE

PRODUCT SPEC

108-133061

APPLICATION SPEC

114-133061

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME

N.S.COOLSPLICE

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-2213800

-

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±0.2
2 PLC	±0.15
3 PLC	±
4 PLC	±
ANGLES	±3°
FINISH	

MATERIAL

SEE NOTES

FINISH SEE NOTES

SCALE 2:1

SHEET 1

OF 1

REV B

1470-19 (3/11)