REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 07/27/10'	~	

N=HALF OF PIN POSISTIONS





RECOMMEND PCB LAYOUT
(TOLERANCE=±0.05)

NOTES:

1. ELECTRICAL CHARACTERISTICS:
   - 1.1 CONTACT RESISTANCE: 20mΩ Max. INITIAL.
   - 1.2 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
   - 1.3 INSULATION RESISTANCE: 1000MΩ Min.
2. ENVIRONMENT CHARACTERISTICS:
   - 2.1 TEMPERATURE: −40°C~+105°C.
3. PART NUMBER: DS1026−07
4. PRODUCT NUMBER CODE:

DS1026−07 − X X X X X X

- POST SUPPORT
  S:W/ POST
  X:W/O POST
- CONTACTS TYPE
  S:SMT
- HOUSING COLOR
  B:BLACK
- CONTACT PLATING
  8: FULL GOLD FLASH
- CONNECTOR TYPE
  S:SOCKET
- No.OF CONTACTS
  2*1−2*X
- SERIES No.
  DS1026−07

Tel:86-574-63508787
Fax:86-574-63510817
E-mail:sale@zhenqin.com.cn
Http://www.connfly.com
Add:East Industry Zone KuangYan
Town Cixi Ningbo China
P.C:315333

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1026-07-2*XXXXX		

PROJECTION		TITLE	DUAL ROW W/N LOCATE PEG S.M.T
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1026-07 SERIES

晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD