

N: NUMBER OF CONTACTS

ORDER INFORMATION

Z B 1 0 0 4 - X X X X

SERIES NO

No. OF CONTACTS
 1x1~1x40
 2x2~2x40
 3x3~3x40

CONTACT PLATING

1: FULL GOLD
 2: FULL NICKEL
 4: GOLD+NICKEL

MOUNTING TYPE
 V: V/T TYPE


PROFILE HEIGHT
 (DIM A)
 1: 5.0MM
 2: 8.5MM

NOTES:

1. ELECTRICAL CHARACTERISTICS:
 - 1.1 CONTACT RESISTANCE: 20mΩ Max. INITIAL.
 - 1.2 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
 - 1.3 INSULATION RESISTANCE: 1000MΩ Min.
2. MECHANICAL CHARACTERISTICS:
 - 2.1 CONTACT RETENTION FORCE: 500gf Min.
3. ENVIRONMENT CHARACTERISTICS:
 - 3.1 TEMPERATURE RANGE: -40°C ~ +105°C.

2.54mm FEMALE HEADER V/T TYPE

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	SK	DATE 2018-5-25	SIZE A4		UNITS 1/1
CHK		DATE	UNITS MM		SCALE
APP		DATE			



NINGBO ZHONGBO PHOTOVOLTAIC TECHNOLOGY CO.,LTD

DWGNO

ZB1004-XP-V