



N:NUMBER OF CONTACTS

ORDER INFORMATION

Z B 1 0 0 3 - X X X - X - X

SERIES NO

No. OF CONTACTS
 1*1~1*40
 2*2~2*40
 3*3~3*40

CONTACT PLATING

1: FULL GOLD
 2: FULL NICKEL
 3: FULL TIN

MOUNTING TYPE
 V: V/T TYPE

PLATING LEVEL
 (FOR GOLD ONLY)
 A: LEVEL A
 B: LEVEL B
 C: LEVEL C

PIN DIM TYPE
 A3.0/B6.1
 A3.5/B17.0

- NOTES:
1. ELECTRICAL CHARACTERISTICS:
 - 1.1 CONTACT RESISTANCE: 20mΩ Max.
 - 1.2 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
 - 1.3 INSULATION RESISTANCE: 1000MΩ Min.
 2. ENVIRONMENT CHARACTERISTICS:
 - 2.1 TEMPERATURE: -40°C~+105°C.

2.54mm PIN HEADER V/T TYPE

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	SK	DATE 2018-5-25	SIZE A4		UNITS 1/1
CHK		DATE	UNITS MM	SCALE	
APP		DATE			

ZHONGBO
 NINGBO ZHONGBO PHOTOVOLTAIC TECHNOLOGY CO.,LTD
 DWGNO ZB1003-XP-V