



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: - 40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Copper Alloy
 Standard: Brass
 Insulator Material: High Temperature Polyester,UL 94V-0

Standard:Gold Flash all over

Recommended P.C. Board Hole Layout

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.							
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名 1.27mm PIN HEADER SINGLE ROW HORIZONTAL SMT						
DWG. 製圖 Hedy	SCALE 比例 參考	<table border="1"> <tr> <td>.X</td> <td>.XX</td> <td>.XXX</td> </tr> <tr> <td>±0.3</td> <td>±0.20</td> <td>±0.100</td> </tr> </table>	.X	.XX	.XXX	±0.3	±0.20	±0.100	TYPE 1XXXP H=1.5mm GOLD FLASH PLATING (C=3.55mm D=2.3mm E=1.27mm) WITHOUT LOCATING PEG BOX PACKING ROHS
.X	.XX	.XXX							
±0.3	±0.20	±0.100							
DATE 制表日 2016/04/14	UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號 C1176-XXADGATDR						
	PAGE 張數 1 / 1	REV. 版次 A							