

SPECIFICATION



Current Rating: 1 AMP
 Insulation Resistance: 1000MΩ Min.
 Contact Resistance: 20mΩ Max.
 Dielectric Voltage: 500V AC for one minute
 Operation Temperature: -40 °C to +105 °C

MATERIAL


Insulator: Hi-Temp. Thermoplastic, UL 94V-0,Black
 Contact Pin: Copper Alloy

ORDER INFORMATION


5 P H 3 D D A 2 5 - 1 X X X X N N X U - A L 1 B - 0 0



Recommended PCB Layout
 (PCB TOLERANCE ±0.05)



Old Part No. : PH3D25-1XX-U



品名 TITLE	PIN HEADER 1.27mm S/R V/T DIP TYPE			頁數 Page	1/1
品號 PART NO.	5PH3DDA25- 1XXXXNNU-XXXXXXXXXX-00		繪圖 DRAWN	Roy 2015/08/19	
圖號 DRAWING NO.	GN016-GA319	版本 REV.	E	核對 CHECKED	Josh 2018/03/23
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/03/23
公差 TOLERANCE	.X ± 0.25 .XX ± 0.20	單位 UNIT	mm	THIRD ANGLE PROJECTION	

△x1	ECN No.:210619 Cancel the top view	Benson	2021/07/10
△x1	ECN No.:180310,Remove the Cap & Revise the Package option .	Roy	2018/03/23
△x1	ECN:170910,Delete the Packing:B:Bag	Kilin	2017/10/31
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE