





Verpackt in Gurtverpackung  
Tape on Reel Packaging  
Verpackungseinheit: 320 Stück  
Packaging unit: 320 pcs



Leiterplatten-Layout Vorschlag für SMT  
PCB-Layout Proposal for SMT




Anforderungsstufe 1  
Performance Level 1

Kontaktbereich vergoldet  
Mating Area gold plating

Anschlussbereich verzinkt 4-6 µm  
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0.1 mm  
Coplanarity Area of Termination ≤ 0.1 mm

← Abspulrichtung - Reel off Direction



454209		weiß white	0.6	9.0	1.2	8.4	Codierung wie Variante schwarz Encoding such variant black
294652		rot red	4.2	5.4	4.8	4.8	
294651		grün green	3.0	6.6	3.6	6.0	
294650		blau blue	1.8	7.8	2.4	7.2	
294649		schwarz black	0.6	9.0	1.2	8.4	
Ident-Nr. part-no.	Codierung coding	Farbe color	A	B	C	D	Bemerkung note

Information:	Tolerances		Scale	3:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation
		www.ERNI.com		M 2.54 SRC-P, 8-polig
30.04.2013		224994		I
Date		Class		A2
SRCP				