



规格/General	公差(Tolerances)	(mm)
0	>3	>6
~	~	~
3	6	10
±0.12	±0.18	±0.22
	±0.26	±0.31
	±0.37	±0.57
	±0.80	±0.93
	±1.05	±1.15
	±1.60	±2.20
	±2.50	
		±Z
		0.1/10

4	Spring	Stainless steel
3	Pin header	Copper Alloy
2	Button	PA66
1	Housing	PA4T
ITEM	NAME OF PART	MATERIAL
UL 标准 /UL Standard:	B	C
额定电压 /Rated Voltage(V)	300/12	/
额定电流 /Rated Current(A)	300/10	300/10
IEC 标准 /IEC Standard:		
过压类别 /Overvoltage Category /污染等级 /Pollution Degree	II/2	III/2
额定电压 /电压 /Rated Voltage(V) /Current(A)	500/17.5	320/17.5
额定零件电压 (KV) /Rate Impulse Voltage(KV)	4	4
线径范围 (绝缘和裸线) /Wire Range(rigid and flexible) (mm ² /AWG)	0.2~1.5	28~14
间距 /Pitch (mm) /线数范围 /Poles	3.50	N=02~24P
引线长度 /Stripping length (mm)		8~9
使用温度范围 /Operating temperature(°C)		-40~+130
符合RoHS环保要求 /Conform to RoHS	Yes	

MATERIAL: /
SURFACE: /

MAT NO.: /

STATUS: /

APPD: LiGL 2020.05.18

CHKD: Mek 2020.05.18

DRAFT: LuoXM 2020.05.18

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
宁波高松电子有限公司

DRAWING NO.: 10000784

TYPE: CUSTOMER DRAWING

SCALE: 1:1

REV T0

SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE

1 2 3 4 5 6