



精度等级/General		Tolerances(mm)										公差	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
3	6	10	18	30	50	80	120	180	250	315	400	500	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

ITEM	NAME OF PART	MATERIAL	NOTES
3	Bridgeware	Copper	
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

间距/Pitch(mm) / 线距/Lead(mm) / 使用温度范围/Operating Temperature(°C)
 5.10/N=02~10P
 -40~+105
 符合RoHS环保要求/Conform to RoHS Yes

MATERIAL: / SURFACE: /

MAT NO.: /
 STATUS: /
 APPD: Li GL 2020.06.04
 CHKD: Moo J 2020.06.04

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO.,LTD**
DFA2.5-XXP-1Y-00A(H)

DRAWING NO.: DFA2.5-C01
 DRAFT:ZhengQG 2020.06.04
 TYPE: CUSTOMER DRAWING
 SCALE: 4:1
 REV T0
 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE

