



公差/General tolerances(mm)		0.1/10
0	>3	~
3	>6	~
6	>10	~
10	>18	~
18	>30	~
30	>50	~
50	>80	~
80	>120	~
120	>180	~
180	>250	~
250	>315	~
315	>400	~
400	>500	~
500	>500	~
±0.12	±0.18	±0.22
±0.26	±0.31	±0.37
±0.57	±0.57	±0.80
±0.93	±1.05	±1.15
±1.60	±2.20	±2.50
±2	±2	±2

ITEM	NAME OF PART	MATERIAL	NOTES
3	Square Nut	Stainless steel	M3/Zn Plated
2	Screw	Stainless steel	M3/Zn Plated
1	Housing	PA66	UL94V-0

螺丝扭矩/Torque Tightening(N·m/Lb.in) M3: 0.5/4.43
 间距/Pitch(mm)/螺距范围/Poles 8.5/01P
 使用温度范围/Operating Temperature(°C) -40~+105
 符合RoHS环保要求/Conform to RoHS Yes

MATERIAL: SURFACE: Yes

MAT NO.: /
 STATUS: /
 APPD: /
 CHKD: /

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
E-MK-01P-1Y-00A(H)

DRAWING NO.: E-MK-C01
 TYPE: CUSTOMER DRAWING
 SCALE: 1:1
 SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE

DRFT: Feng X 2020.06.09
 SIZE: A4
 (mm)
 (inch)

A B C D 1 2 3 4 5 6