



Home > Products > Discrete Thermistors > 143 > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

143-102LAG-A01



5,08 mm [0.2 in] Disc thermistor with leads

Actual product appearance may vary.

Features

Cost effective
 PC board mountable
 Rugged design
 Versatile
 Solderable leads
 Available on tape and reel

Potential Applications

Low-cost applications with a maximum temperature of 150 °C [302 °F]
 PCB temperature sensing
 Automotive

Description

140 Series, 142 Series and 143 Series Thermistors are available in a broad range of custom resistance values and R/T curves. Leads are uninsulated. Diameters range from 2,54 mm [0.1 in] to 10,16 mm [0.4 in]. They are available on tape and reel.

Supporting Documentation

None Available

Product Specifications	
Availability	Global
Nominal Resistance at 25 °C [77 °F]	1,000 Ohm
Tolerance	± 10.0%
Accuracy	25 °C [77 °F]
R- T Curve	16
Operating Temperature Range	-60 °C to 125 °C [-76 °F to 257 °F]
Maximum Diameter	5,08 mm [0.20 in]
Termination Material	Tinned copper
Lead length	38,1 mm [1.50 in]
Time Constant in Air	16.0 s
Dissipation Constant	4,0 m/W°C
Series Name	143

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

[Specification Search](#)