


SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:			
PART NO: LCB2012-601Y-N				DWG.NO: TE1003027			
CUSTOMER PART NO:				CUST.DWG.NO:			
(1) DIMENSIONS (UNIT: mm) 				A	2.0 ± 0.2	m/m	
				B	1.2 ± 0.2	m/m	
				C	0.9 ± 0.2	m/m	
				D	0.5 ± 0.3	m/m	
				E		m/m	
				F		m/m	
				G		m/m	
				H		m/m	
				I		m/m	
				J		m/m	
(2) ELECTRICAL REQUIREMENTS							
Z (Ω)	600 ± 25%	TEST FREQ	100MHz / 100mV				
RDC (Ω)	0.15 (MAX)	TEST FREQ					
IDC (mA)	2000 (MAX)	TEST FREQ					
TEST INSTRUMENTS HP4338A MILLIOHMMETER HP4291B RF IMPEDANCE/MATERIAL ANALYZER				APPROVED BY <div style="text-align: right;">吳載敏</div>			
				CHECKED BY <div style="text-align: right;">張明德</div>			
				DRAWN BY <div style="text-align: right;">黃慧診</div>			

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER :				DATE :					
PART NO: LCB2012-601Y-N				DWG.NO: TE1003027					
CUSTOMER PART NO :				CUST.DWG.NO :					
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)	DIMENSION (UNIT : mm)					
FREQ	100MHz /100mV			A	B	C	D		
SPEC	600 $\pm 25\%$	0.15 (MAX)	2000 (MAX)	2.0 ± 0.2	1.2 ± 0.2	0.9 ± 0.2	0.5 ± 0.3		
1	602.6	0.075	OK	2.01	1.24	0.90	0.52		
2	647.0	0.075	OK	2.05	1.22	0.88	0.50		
3	604.5	0.074	OK	2.03	1.23	0.89	0.50		
4	601.1	0.074	OK	2.04	1.22	0.90	0.52		
5	637.1	0.073	OK	2.02	1.22	0.92	0.52		
6	612.8	0.076	OK	2.01	1.24	0.91	0.49		
7	632.3	0.075	OK	2.05	1.22	0.91	0.51		
8	622.8	0.073	OK	2.03	1.23	0.92	0.53		
9	632.2	0.074	OK	2.02	1.22	0.88	0.50		
10	628.4	0.074	OK	2.02	1.25	0.90	0.52		
\bar{X}	622.1	0.074		2.03	1.23	0.90	0.51		
R	45.9	0.003		0.04	0.03	0.04	0.04		
						APPROVED BY			
						吳載敏			
						CHECKED BY			
						張明德			
						DRAWN BY			
						黃慧診			

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

LCB2012-601Y-N

