


SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:	
PART NO: CB1608-700Y-N				DWG.NO: TE2000046	
CUSTOMER PART NO:				CUST.DWG.NO:	
(1) DIMENSIONS (UNIT: mm) 				A	1.6 ± 0.2 m/m
				B	0.8 ± 0.2 m/m
				C	0.8 ± 0.2 m/m
				D	0.3 ± 0.2 m/m
				E	m/m
				F	m/m
				G	m/m
				H	m/m
				I	m/m
				J	m/m
(2)ELECTRICAL REQUIREMENTS					
Z (Ω)	70 ± 25%	TEST FREQ	100MHz / 100mV		
RDC (Ω)	0.2 (MAX)	TEST FREQ			
IDC (mA)	300 (MAX)	TEST FREQ			
TEST INSTRUMENTS HP4338A MILLIOHMMETER HP 4291B RF IMPEDANCE/MATERIAL ANALYZER				APPROVED BY 吳載敏	
				CHECKED BY 張明德	
				DRAWN BY 黃慧診	

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB: www.coremaster.com.tw

TEST DATA

CUSTOMER :				DATE :					
PART NO: CB1608-700Y-N				DWG.NO: TE2000046					
CUSTOMER PART NO :				CUST.DWG.NO :					
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)	DIMENSION (UNIT : mm)					
FREQ	100MHz / 100mV			A	B	C	D		
SPEC	70 $\pm 25\%$	0.2 (MAX)	300 (MAX)	1.6 ± 0.2	0.8 ± 0.2	0.8 ± 0.2	0.3 ± 0.2		
1	56.4	0.032	OK	1.60	0.79	0.79	0.29		
2	57.8	0.031	OK	1.62	0.80	0.81	0.31		
3	58.3	0.032	OK	1.61	0.79	0.80	0.29		
4	59.0	0.032	OK	1.60	0.81	0.79	0.30		
5	57.6	0.030	OK	1.63	0.80	0.81	0.29		
6	56.5	0.032	OK	1.60	0.79	0.79	0.30		
7	58.7	0.030	OK	1.61	0.81	0.80	0.31		
8	58.5	0.031	OK	1.60	0.79	0.79	0.29		
9	60.1	0.030	OK	1.62	0.80	0.81	0.29		
10	59.2	0.032	OK	1.60	0.79	0.80	0.31		
X	58.2	0.031		1.61	0.80	0.80	0.30		
R	3.7	0.002		0.03	0.02	0.02	0.02		
						APPROVED BY 吳載敏			
						CHECKED BY 張明德			
						DRAWN BY 黃慧診			

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB: www.coremaster.com.tw

CB1608-700Y-N

