


# SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:			
PART NO: CB1608-601Y-N				DWG.NO: TE2003184			
CUSTOMER PART NO:				CUST.DWG.NO:			
(1) DIMENSIONS (UNIT: mm)  				A	1.6 ± 0.2	m/m	
				B	0.8 ± 0.2	m/m	
				C	0.8 ± 0.2	m/m	
				D	0.3 ± 0.2	m/m	
				E		m/m	
				F		m/m	
				G		m/m	
				H		m/m	
				I		m/m	
				J		m/m	
(2) ELECTRICAL REQUIREMENTS							
Z (Ω)	600 ± 25%	TEST FREQ	100MHz / 100mV				
RDC (Ω)	0.45 (MAX)	TEST FREQ					
IDC (mA)	200 (MAX)	TEST FREQ					
TEST INSTRUMENTS HP4338A MILLIOHMMETER HP4291B RF IMPEDANCE/MATERIAL ANALYZER				APPROVED BY 吳載敏			
				CHECKED BY 張明德			
				DRAWN BY 黃慧診			

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-8919-1288    FAX:886-2-8919-1298    WEB: www.coremaster.com.tw

# TEST DATA

CUSTOMER :				DATE :					
PART NO: CB1608-601Y-N				DWG.NO: TE2003184					
CUSTOMER PART NO :				CUST.DWG.NO :					
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)	DIMENSION (UNIT : mm)					
				A	B	C	D		
FREQ	100MHz / 100mV								
SPEC	600 ± 25%	0.45 (MAX)	200 (MAX)	1.6 ± 0.2	0.8 ± 0.2	0.8 ± 0.2	0.3 ± 0.2		
1	525.1	0.281	OK	1.60	0.80	0.80	0.30		
2	544.7	0.243	OK	1.64	0.82	0.83	0.32		
3	543.8	0.262	OK	1.60	0.80	0.82	0.30		
4	565.5	0.255	OK	1.61	0.81	0.81	0.32		
5	535.5	0.251	OK	1.62	0.84	0.80	0.31		
6	555.5	0.255	OK	1.60	0.82	0.81	0.34		
7	531.0	0.265	OK	1.65	0.80	0.82	0.32		
8	561.2	0.250	OK	1.61	0.83	0.81	0.30		
9	520.1	0.257	OK	1.60	0.80	0.80	0.31		
10	519.0	0.260	OK	1.62	0.81	0.81	0.32		
$\bar{X}$	540.1	0.258		1.62	0.81	0.81	0.31		
R	46.5	0.038		0.05	0.04	0.03	0.04		
						APPROVED BY			
						吳載敏			
						CHECKED BY			
						張明德			
						DRAWN BY			
						黃慧診			

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-8919-1288    FAX:886-2-8919-1298    WEB: www.coremaster.com.tw

# CB1608-601Y-N

