PRODUCT DATA APPROVAL SHEET



Core- EE15330P

Cosmo Ferrites Ltd. - INDIA

Appearance & Shape: To be free from any defect such as flow, burrs, unevenness etc, As per IEC standards. **Effective Parameters irrespective of material grade (per set)**

Effective Length (L_e): 223.7mm
Effective Area (A_e): 1163.1mm²
Effective Area (A_{Min}): 1156.6mm²
Effective Volume (V_e): 260185mm³
Approximate weight: 1454.0g/Set




EE15330P (Un-gapped)

Test Conditions: 1kHz/1mT/CFR COIL,N=10/25°C

Material Grade	Initial Permeability (μ _{iac})	AL Value (nH)/Set	Ordering code
CF139	2100 ±20%	11400 +30%/-20%	CF139EE15330P

Dimensions:

Dimension	Nominal	Maximum	Minimum
	(in mm)	(in mm)	(in mm)
Α	153.0	155.0	151.0
В	129.0	131.0	127.0
С	31.0	31.5	30.5
D	21.0	21.75	20.25
E	22.0	22.5	21.5
F	55.0	55.8	54.2



For Cosmo Ferrites Limited-INDIA

Checked By: R.S. Approved By: B.S. Authorized By: KSR

Date: 20-12-2020 (ISSUE NO.1)

Customer's Approval Authorized Signatory:

Name: Date:

NOTE: <u>Please send this Data Sheet back to Cosmo Ferrites Ltd. after approval. If not received back within 15 days, it will be presumed that all the specifications given in the consent/data sheet are acceptable to the concerned.</u>