



SPECIFICATION FOR APPROVAL

CUSTOMER:		DATE:
PART NO: SRI0605B-560M		DWG.NO: DL0120511
CUSTOMER PART NO:		CUST.DWG.NO:
(1) DIMENSION(UNIT: mm) 		A 6.6 ± 0.3 m/m
		B 6.2 ± 0.3 m/m
		C 5.0 (MAX) m/m
		D 4.0 (REF) m/m
		E 1.5 (REF) m/m
		G 2.5(REF) m/m
		H 1.8(REF) m/m
		L 7.0(REF) m/m
		(2)ELECTRICAL REQUIREMENTS
L (uH)	56 ± 20%	
RDC (Ω)	0.44 (MAX)	
IDC (A)	1.2 (MAX)	
TEST CONDITION	1KHZ / 1V	
(4)MATERIAL LIST		
NO/ITEM	MATERIAL	SUPPLIER
CORE	DR4×4.4 B2.4 F3.2 RI6.2×4.3×4.4 或同等級	昱欣
WIRE TYPE	2UEW φ 0.16m/m 或同等級	上海中馬
WINDING	40.5TS (REF)	
BASE	電木 LS-B067 或同等級	碩誠
		APPROVED BY 吳載敏
		CHECKED BY 張明德
		DRAWN BY Vicky

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER:				DATE:			
PART NO: SRI0605B-560M				DWG.NO: DL0120511			
CUSTOMER PART NO :				CUST.DWG.NO :			
TEST CONDITION: 1KHZ / 1V				DIMENSION (UNIT : mm)			
ITEM	L (uH)	RDC (Ω)	IDC (A)	A	B	C	
SPEC	56 ± 20%	0.44 (MAX)	1.2 (MAX)	6.6 ± 0.3	6.2 ± 0.3	5.0 (MAX)	
1	57.0	0.36	OK	6.53	6.25	4.77	
2	56.2	0.36	OK	6.58	6.27	4.81	
3	56.7	0.38	OK	6.59	6.24	4.80	
4	56.1	0.37	OK	6.58	6.20	4.82	
5	56.3	0.36	OK	6.57	6.23	4.78	
6	56.0	0.37	OK	6.63	6.21	4.83	
7	55.9	0.38	OK	6.62	6.24	4.81	
8	56.7	0.38	OK	6.61	6.25	4.82	
9	56.3	0.37	OK	6.63	6.25	4.77	
10	55.8	0.37	OK	6.62	6.27	4.79	
X	56.3	0.37		6.60	6.24	4.80	
R	1.2	0.02		0.10	0.07	0.06	
TEST INSTRUMENTS HIOKI3532-50 LCR METER VR-131 RDC METER VR116+VR7220 BA/S CURRENT				APPROVED BY			
				吳載敏			
				CHECKED BY			
				張明德			
				DRAWN BY			
				Vicky			


CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

INDUCTANCE VS CURRENT

CUSTOMER:	DATE:
PART NO: SRI0605B-560M	DWG.NO: DL0120511
CUSTOMER PART NO :	CUST.DWG.NO :

CURRENT VS INDUCTANCE					
IDC(A)	INDUCTANCE(uH)				
0	56.7				
0.4	53.6				
0.8	49.2				
1.2	44.8				
1.5	40.2				



APPROVED BY 吳載敏	CHECKED BY 張明德	DRAWN BY Vicky
--------------------	-------------------	-------------------