

Aluminum Electrolytic Capacitor Specification

Series	KR1	63 V 2200 μ F	Part No.	KR1-063V222MJ350
Customer No.	337141		Case size	Φ D16X L 35
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 85 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.11 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 1386 μ A (20 $^{\circ}$ C 63 V 2 min)	
	Ripple current (MAX)		2080 mArms (120Hz , 85 $^{\circ}$ C)	
	Impedance (MAX)		/	
	Load life		2000 hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p>The drawing shows a side view of the capacitor with a sleeve. Labels include: Vent, Sleeve, Copper clad steel wire(tinned), Markings, $\Phi 0.8 \pm 0.05$, 16 ± 0.5 MAX, 35 ± 2.0 max, 15min, 4min, and polarity symbols \oplus and \ominus. The end view shows a circular cross-section with a lead space of 7.5 ± 0.5 mm and two terminals. The unit is specified as (unit):mm.</p>			
Recorder	(The first edition) :2016-5-18			
Wrote by: Luoli		Checked by: Dingchanghua		Approved by: Shenzhihong