

Aluminum Electrolytic Capacitor Specification

Series	KRM	35 V 220 μ F	Part No.	KRM-035V221MF115-T/A5.0
Customer No.	/		Case size	Φ D 8 X L 11.5
Specification	Items		Standard	
	Operating temperature range		- 55 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.12 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 77 μ A (20 $^{\circ}$ C 35 V 1 min)	
	Impedance (MAX)		/	
	Ripple current (MAX)		270 mArms (120Hz , 105 $^{\circ}$ C)	
	Load life		2000hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p>The drawing shows a side view of the capacitor with the following dimensions and labels: <ul style="list-style-type: none"> Side View: <ul style="list-style-type: none"> Height: 8+0.5 MAX Length: 11.5 + 1.5max Terminal length: 15min Terminal diameter: 4min Wire diameter: Φ0.5\pm0.05 Labels: Vent, Sleeve, Markings, Copper clad steel wire(tinned) Terminal polarity: \oplus and \ominus Top View: <ul style="list-style-type: none"> Lead space: 3.5\pm0.5 Material: Flat Rubber Remarks: Taping space: 5.0 (+0.8-0.2) Unit: (unit):mm </p>			
Recorder	(The first edition) : 2017-4-24			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG