

Aluminum Electrolytic Capacitor Specification

Series	KRM	16 V 220 μ F	Part No.	KRM-016V221MF115-T/A5.0
Customer No.	/		Case size	Φ D 8 X L 11.5
Specification	Items		Standard	
	Operating temperature range		- 55 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.16 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 35.2 μ A (20 $^{\circ}$ C 16 V 1 min)	
	Impedance (MAX)		/	
	Ripple current (MAX)		215 mArms (120Hz , 105 $^{\circ}$ C)	
	Load life		2000hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p>The drawing shows a side view of the capacitor with a sleeve. Labels include: Vent, Sleeve, Markings, Copper clad steel wire(tinned), $\Phi 0.5 \pm 0.05$, and polarity symbols (+ and -). Dimensions are: 8+0.5 MAX (height), 11.5 +1.5max (length), 15min (lead length), and 4min (lead diameter). A top view shows a circular capacitor with two leads and a 'Flat Rubber' label. A note states: 【Remarks:Taping space: 5.0 (+0.8-0.2)】 and (unit):mm.</p>			
Recorder	(The first edition) : 2017-4-24			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG