

KOSHIN

Aluminum Electrolytic Capacitor Specification				
Series	KR2	10 V 100 μ F	Part No.	KR2-010V101MC070-T/A5.0
Customer No.	/		Case size	Φ D 5 X L 7
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 85 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.19 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 10 μ A (20 $^{\circ}$ C 10 V 2 min)	
	Impedance (MAX)		\	
	Ripple current (MAX)		78 mA/rms (120Hz , 85 $^{\circ}$ C)	
	Load life		1000 hrs	
Outline	Sleeve color		Blue	
	Marking color		Black	
	(Dimensions)			
	<div><div><p>Copper clad steel wire(tinned)</p><p>5+0.5 MAX</p><p>Markings</p><p>7 + 1.0 max</p><p>15min</p><p>4min</p><p>Φ0.5\pm0.05</p></div><div><p>Flat Rubber</p><p>Taping space 5.0 (+0.8-0.2)</p></div></div> <p>(unit):mm</p>			
Recorder	(The first edition) : 2015-7-16			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG